



## HOT AIR STERILIZER BSHA-103

## HOT AIR STERILIZER BSHA-103

Durable, corrosion resistant and easy to clean stainless steel design in a wide range of capacities. Our hot air sterilizers are microprocessor controlled and perform reliably. Digital display with broad observation window allows easy operation.

Used in Widely used for dry heat sterilisation of glasswares, instruments and equipments in laboratories and hospitals..

## BSHA-103 HOT AIR STERILIZER

- Corrosion free stainless steel interiors
- Digital display with touch buttons
- Auto save option for power failure
- Safety alarm for temperature rise and timer
- Adjustable shelves and wide observation window
- Microprocessor controls for temperature uniformity
- Door with seal and heat insulation to prevent heat loss

## SPECIFICATIONS

Model	BSHA-103
Capacity	70 L
Temperature Range	RT+5°C to 250°C
Temperature Accuracy	±1°C
Temperature Fluctuation	±1°C (100°C)
Temperature Uniformity	±1°C (100°C)
Temperature Display Resolution	1°C
Timer Range	0-999 min
Inner Dimension	450x400x450 mm
Overall Dimension (LxWxH)	740x530x630 mm
Shelves	2
Power	1100 W
Power Supply	220±10%, 50Hz±2%



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)