



ORBITAL SHAKER BSOT-301

ORBITAL SHAKER BSOT-301

Our product is an accurately designed, microprocessor controlled with double Decker platform to save your valuable lab space. Three eccentric shaft balancing drive ensures shaking with uniform speed. Speed adjustment settings permit both gentle and vigorous shaking. Varieties of platforms are available for different glassware and vessels. Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions. Also known as Laboratory Orbital Shaker.

BSOT-301 ORBITAL SHAKER

Compact space-saving design fits easily in incubator and refrigerator
Simultaneous display of speed, timer and operating mode
Brushless DC motor ensures maintenance-free, reliable and quiet operation
Electronic time switching clock controls time or continuous operation mode
RS232 interface enables data logging & computer control
Over speed detection and protection
Accommodate a variety of platforms, non-slip rubber mat, conical flasks and other sample containers

SPECIFICATIONS

Model	BSOT-301
Speed Range	0-200 rpm
Temperature	4-40°C
Permissible Ambient Temperature	5-40°C
Shaking Orbit	20 mm
Permissible Relative Humidity	80.00%
Motion	Orbital/Linear
Motor rating Input	16 W
Motor rating output W	10
Maximum Load Capacity	3 kg
Operation	Continuous
Overall Dimension	330x270x110 mm
Display	Analog
Weight	3.1 kg
Power	30 W
Power Supply	100-240 V, 50/60 Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com