



THERMO SHAKER INCUBATOR BSTH-104

THERMO SHAKER INCUBATOR BSTH-104

Used in Incubation, Cultivation, Re-suspending Pellets, Denaturin, PCR preparations, ELISA Assays, Colorimetric Assays, Enzyme, Protein Analysis.

Also known as Thermo Shaker, Lab Shaker, Thermo Shaker Incubator, Laboratory Thermo Shaker Incubator.

BSTH-104 THERMO SHAKER INCUBATOR



Optimized 2D mixing designed for simultaneous mixing and vortexing applications
Pre-programmed soft keys and reliable universal holder
Automatic imbalance detection and anti-spill technology
Mixing in a 3-in-1 format: Plates (up to 96-well and 384-well formats), Micro-Tubes, vortexing numerous tube formats
Custom blocks available for different experiment needs

SPECIFICATIONS

Model	BSTH-104
Speed Range	200~1200 rpm
Shaking Orbit	3 mm (horizontal)
Temp. Control Range	R.T.+5°C ~70°C
Temp. Setting Range	5°C~70°C
Temp. Stability@37°C	±0.2°C
Platform Temp. Uniformity	±0.5°C
Temp. Display Accuracy	0.1°C
Heating Speed Range	<25 min (20°C to 70°C)
Timing Range	1 min~99 h 59 min or short mix
Sample Capacity	2 Pieces of Plates (Height<35mm)
Voltage	AC 220V/AC 110V, 50/60 Hz
Power	150 W
Fuse	250 V, 1 A/2 A, φ5x20
Overall Dimension	W.284 x D.264 x H.157mm
Net Weight	6.7 kgs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com