



STABILITY TEST CHAMBER BTST-104

STABILITY TEST CHAMBER BTST-104

Stability test chamber is a reliable solution for managing stability and stress testing. Designed with laser processing technology and microprocessor controlled, it gives you interruption free long term operation. Durable interiors along with safety features make it an ideal option.

Used in Widely used for checking corrosion resistance of surface coatings and paints.

Also known as Stress Testing Chamber, Laboratory Stability Test Chamber.

BTST-104 STABILITY TEST CHAMBER

Durable glass strengthened plastic with wall spray system

Corrosion resistant interiors

Unique nozzle in spray duct

Transparent lid optimizes test observation

SPECIFICATIONS

Model	BTST-104
Capacity	750 L
Temperature Range	RT to 55°C
Temperature Uniformity	±2°C
Temperature Fluctuation	±0.1°C
Temperature Resolution	0.1°C
Humidity Range	20~ 95% RH
Humidity Fluctuation	Within ±1.5% (65°C)
Sedimentation	1-2ml/80m2.h
Shelves	4
Water Supply Volume	Inside: 10 L Outside: 25 L
Overall Dimension	1100x750x600 mm
Power	3000 W
Power Supply	AC-220V 50/60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com