



STABILITY TEST CHAMBER BTST-1502

STABILITY TEST CHAMBER BTST-1502

BTST-1502 STABILITY TEST CHAMBER



Microprocessor control, stainless steel chamber, semicircular arcs at corners for easy cleaning
Even air circulating system
R134a refrigerant, 2 imported compressors and fan motor
Over temperature and temperature difference alarms
Imported humidity sensor which can be used in high humidity environment
Balance temperature and humidity adjusting system
There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement
UV light system for periodic sterilization of chamber.(Option)
Independent audible and visible temperature-limiting alarm system ensures experiments run safely
RS485 connector can connect computer record and inspect the parameters and the variations of temperature

SPECIFICATIONS

Model	BTST-1502
Capacity	150 L
Temperature Range	0-65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C
Humidity control range	35-95%RH
Humidity Stability	±3%RH
Timing Range	1-99 hours each period
Humidity and temp adjusting	Balance temperature and humidity adjusting
Cooling system/cooling mode	Two sets of imported compressor work rotationally
Controller	Programmable(LCD screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5-30°C
Electrical Requirement	AC 220 V 50 Hz
Power Consumption	2100 W
Interior Dimension	550Wx405Dx670H mm
External Dimension	690Wx805Dx1530H mm
Shelves	3 pcs
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection Over temperature protection, Overload protection, Water protections



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com