



## STABILITY TEST CHAMBER BTST-1606

# STABILITY TEST CHAMBER BTST-1606

## BTST-1606 STABILITY TEST CHAMBER



- Microprocessor control, stainless steel chamber, semicircular arcs at corners for easy cleaning
- Even air circulating system
- R134a refrigerant, 2 imported compressors and fan motor
- Over temperature and temperature difference alarms
- Imported humidity sensor which can be used in high humidity environment
- Balance temperature and humidity adjusting system
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement
- UV light system for periodic sterilization of chamber.(Option)
- Independent audible and visible temperature-limiting alarm system ensures experiments run safely
- RS485 connector can connect computer record and inspect the parameters and the variations of temperature

## SPECIFICATIONS

Model	BTST-1606
Capacity	1000 L
Temperature Range	0-65°C
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C
Humidity control range	40-95%RH
Humidity Stability	±3%RH
Cooling system cooling mode	Two sets of imported compressor work rotationally
Controller	Programmable ( touch screen)
Sensor	Temp: Pt100, Humidity: capacitance sensor
Ambient Temperature	RT+5-30°C
Electrical Requirement	AC 380 V 50 Hz
Power Consumption	7150 W
Interior Dimension	1050Wx590Dx1650H mm
External Dimension	1610Wx890Dx2000H mm
Shelves	4 pcs
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection Over temperature protection, Overload protection, Water protections



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)