



STABILITY TEST CHAMBER BTST-405-E

STABILITY TEST CHAMBER BTST-405-E

Stability test chamber is a reliable solution for managing stability and stress testing. Designed with laser processing technology and microprocessor controlled, it gives you interruption free long term operation. Durable interiors along with safety features make it an ideal option.

Used in Especially designed to perform shelf life and stability studies on drug substances and drug products. Compatible for long term stability test for food and vaccines..

Also known as Stress Testing Chamber, Laboratory Stability Test Chamber.

BTST-405-E STABILITY TEST CHAMBER

Ambient temperature detection function

Imported Honeywell PT1000 temperature sensor for more precise temperature control

Fixed value and program control

With automatic start, automatic stop, timed operation, clock display function

Door switch monitoring function

Five-level automatic defrosting function, and manual defrosting function

Logging function Ambient temperature detection function

Fault monitoring, alarm, recording function (applicable to touch screen model only)

Level 4 password function: login password, operator password, administrator password, senior administrator password (applicable to touch screen model only)

Three power-off mode selection functions: power-off recovery, stop or restart (applicable to touch screen model only)

Curve display function (applicable to touch screen model only)

GPRS SMS alarm function (applicable to touch screen model only)

Real-time data and historical data printing (applicable to touch screen model only)

Touch screen data storage function; an ambient temperature detection function (applicable to touch screen model only)

Optional computer monitoring software for connecting 6 devices with temperature calibration

Water level monitoring and automatic water replenishment function (controlled humidity type)

SPECIFICATIONS

Model	BTST-405-E
Capacity	1100 L
Temperature Range	0~70°C
Temperature Accuracy	0.1°C
Temperature Uniformity	±0.8°C (at 40°C)
Temperature Sensor	Import Honeywell PT1000
Frost-free area	Frost-free operation above 20°C
Defrosting method	Level 5 automatic defrost and manual defrost
Illumination Range	10~10000 Lux
Ultraviolet irradiance	80~100 µw/cm²
Display Resolution	LCD display
Test hole	Left and right double test holes
Log, audit trail function	No
Real-time data, data history monitoring and printing functions	No

Curve display function	No
Level 4 permissions	No
Data storage function	No
Fault monitoring, alarm, recording	No
Shelves	4 shelves
Inner Dimension	1250x735x1200 mm
Overall Dimension	1430x1195x1800 mm
Weight (Net/Gross)	256 kg
Insulation Material	Polyurethane foam
Programm Control	Fuzzy intelligent P.I.D control
Cooling po Wer	1000 W
Heating tube po Wer	2500 W
Power Supply	220V 50/60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com