PRODUCT CATALOG

DIGITAL DISPLAY ULTRASONIC CLEANER BULC-303

ISO9001 CERTIFIED

www.biolabscientific.com

DIGITAL DISPLAY ULTRASONIC CLEANER BULC-303

Digital Display Ultrasonic Cleaner uses frequency of 40Khz for cleaning the lab equipments.
Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

BULC-303 DIGITAL DISPLAY ULTRASONIC CLEANER

- Digital display and control
- Industrial high Q transducers, cleaning conversion efficiency is higher
- No stud- welding technology, Cleaning effect is better
- MCU SWEEP multi frequency ultrasonic generator output, frequency sweep drive ultrasonic cleaning effect more powerful
- MHC heating system, maximum temperature is up to 80°C
- All stainless steel material inner tank is made by punching SUS304 1.0mm
- 2500V high voltage test to ensure the product safety, strict production, aging production quality control

SPECIFICATIONS

Model	BULC-303
Capacity	2 L
Working frequency	40 Khz
Ultrasonic Power	70 W
Heating power	100 W
Timing time	10- 600s
Temperature range	0- 80°C
Cover	Yes
Drain valve	No
Washing basket	Optional
Inner tank dimension	150x135x100 mm
Packing size	242x227x275 mm
Gross weight	2.7 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz

Biolab Scientific Ltd.
3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com