



## DIGITAL DISPLAY ULTRASONIC CLEANER BULC-304

# DIGITAL DISPLAY ULTRASONIC CLEANER BULC-304

Digital Display Ultrasonic Cleaner uses frequency of 40Khz for cleaning the lab equipments.  
Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

## BULC-304 DIGITAL DISPLAY ULTRASONIC CLEANER



Digital display and control

Industrial high Q transducers, cleaning conversion efficiency is higher

No stud- welding technology, Cleaning effect is better

MCU SWEEP multi frequency ultrasonic generator output, frequency sweep drive ultrasonic cleaning effect more powerful

MHC heating system, maximum temperature is up to 80°C

All stainless steel material inner tank is made by punching SUS304 1.0mm

2500V high voltage test to ensure the product safety, strict production, aging production quality control

## SPECIFICATIONS

Model	BULC-304
Capacity	3.2 L
Working frequency	40 Khz
Ultrasonic Power	120 W
Heating power	100 W
Timing time	1- 99 mins
Temperature range	0- 80°C
Cover	Yes
Drain valve	No
Washing basket	Optional
Inner tank dimension	240x135x100 mm
Packing size	342x240x310 mm
Gross weight	4.77 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)