



## DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BULC-802

## DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BULC-802

Double adjustable frequencies ultrasonic cleaner uses frequency of 45 KHz /80 KHz with strong penetrating power and an appropriate cleaning solvent to clean items.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

## BULC-802 DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER



Over- Voltage and over current protection

Standard basket and lid

Low level water protection

Fully microprocessor controller and programmable

Time and temperature real time display

Standard power supply AC220+10%, 50/60Hz: 110V+10%, 60Hz

## SPECIFICATIONS

Model	BULC-802
Capacity	13 L
Adjustable ultrasonic frequency	45 KHz /80 KHz
Time range/ Heating temp	1-480 mins /0- 80°C
Ultrasonic power	300 W
Heating power	400 W
Tank size	300x240x180 mm
Packing Size	840x670x730 mm
Gross Weight	73 Kg



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)