



DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BULC-807

DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BULC-807

Double adjustable frequencies ultrasonic cleaner uses frequency of 45 KHz /80 KHz with strong penetrating power and an appropriate cleaning solvent to clean items.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

BULC-807 DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER



- Over- Voltage and over current protection
- Standard basket and lid
- Low level water protection
- Fully microprocessor controller and programmable
- Time and temperature real time display
- Standard power supply AC220+10%, 50/60Hz: 110V+10%, 60Hz

SPECIFICATIONS

Model	BULC-807
Capacity	27 L
Adjustable ultrasonic frequency	45 KHz /80 KHz
Time range/ Heating temp	1-480 mins /0- 80°C
Ultrasonic power	700 W
Heating power	800 W
Tank size	500x300x180 mm
Packing Size	1100x690x800 mm
Gross Weight	104 Kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com