



DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BULC-816

DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BULC-816

Double adjustable frequencies ultrasonic cleaner uses frequency of 45 KHz /80 KHz with strong penetrating power and an appropriate cleaning solvent to clean items.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

BULC-816 DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER



- Over- Voltage and over current protection
- Standard basket and lid
- Low level water protection
- Fully microprocessor controller and programmable
- Time and temperature real time display
- Standard power supply AC220+10%, 50/60Hz: 110V+10%, 60Hz

SPECIFICATIONS

Model	BULC-816
Capacity	8 L
Adjustable ultrasonic frequency	45 KHz /80 KHz
Time range/ Heating temp	1-480 mins / RT-80°C
Ultrasonic power	200 W
Heating power	400 W
Tank size	300x150x180 mm
Packing Size	500x350x480 mm
Gross Weight	15.5 Kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com