BioLAB

PRODUCT CATALOG

PLATELET INCUBATOR

CE ISO9001 CERTIFIED

www.biolabscientific.com

PLATELET INCUBATOR

Platelet incubators are microprocessor integrated systems designed to provide excellent stability of temperature for storage of platelet concentrates. Forced air circulation maintains uniform temperature throughout the unit.
Used in Biochemical Studies, Hematological Studies, Bacterial Culturing, Research, Microbiological Determinations, Pharmaceutical Stability Assays, Food Processing Quality Control.
Also known as Laboratory Platelet Incubator.

700 PLATELET INCUBATOR

SPECIFICATIONS

Model	BINC-701	BINC-702
Capacity	5 L/cu.ft	10 L/cu.ft
Cooling Method	Forced air cooling	
Defrost	No frost	
Refrigerant	R134a	
Temperature range	20~24°C	
Ambient temperature	10~32°C	
Compressor brand/QTY	EMBRACO/1	
Temperature controller	Microprocessor PID	
Sensor	NTC	
Display	Digital display	
Inside material	SUS	
Outside material	Colored Spray Steel	
Insulation Materials	PU	
Bloodbags(450ml)/Drawer	10 /5 layers	20 /10 layers
NT./GT.	65/87 Kg	85/108.5
Alarm System	High/low temperature, Power failure, Sensor malfunction, Door ajar, Power failure backup system(alarm)-72h	
Accessories	Caster, Outer door / Type - 1Foamed glass door,Test hole - Optional, Light - UV Light, Temperature recorder - Optional	
Shelf/drawer QTY	Drawer	
Internal Dimension	427Wx360Dx467H mm	432Wx462Dx728H mm
Exterior size	520Wx640Dx1030H mm	520Wx640Dx1290H mm
Package size(WxDxH)	590x695x1210 mm	575x690x1450 mm
CBM	0.5	0.58

20GP/40GP/40HQ	24/48/96	32/68/68
Noise	49 db	50 db
Power consumption (kWh/24h)	2.69 (kWh/24h)	4.4 (kWh/24h)
Voltage/frequency	220/50Hz	
Power	197 W	280 W
Current	0.9 A	1.27 A

BINC-701

BINC-702

Biolab Scientific Ltd.
3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com