



PLATELET INCUBATOR

PLATELET INCUBATOR BEZ1BD1

22°C PLATELET SHAKING INCUBATOR



Accurate microprocessor controller makes the inside temperature within $\pm 22 \pm 2^\circ\text{C}$ and resolution 0.1°C .

Suggested ambient temperature: $+10 \sim 32^\circ\text{C}$.

Stainless steel inner chamber and shelves for friendly use and easy cleaning.

Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.

Toughened glass door with self-close function.

Wide available voltage range: $220\text{V} \pm 10\%$.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to power the controller and save temp. data when power failure or system error.

SPECIFICATIONS

Model	BEZ1BD1
Old Model	BINC-701
Temperature Range	$20 \sim 24^\circ\text{C}$
Ambient Temperature	$10 \sim 32^\circ\text{C}$
Capacity (L / Cu. Ft.)	108 / 3.81
Interior Dimensions (WxDxH) mm	427x360x467
Exterior Dimensions (WxDxH) mm	522x600x1035
Weight	65 kgs
Noise	49 dB
Oscillation Range	50 mm
Oscillation Frequency	60 times/min
Max Loading of 450ml Blood Bag	10 Bags
Controller	Microprocessor
Display	LCD
Sensor	NTC
Voltage and Frequency	$220\text{V} \pm 10\%$, 50/60Hz
Power	197 W
Electric Current	1.3 A
Power Consumption (kWh/24h)	2.7
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	EMBRACO / 1
Refrigerant / Weight	R134a / 53g
Door (pcs)	Self-closing Foamed Glass Door / 1
Drawer (pcs)	5
Interior Cabinet Material	Stainless Steel

Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (845mm)
Door Lock	Yes
LED Lamp	UV Lamp
Test Hole (pcs)	Optional
Castors (pcs)	4
Temperature Printer	Yes
Remote Alarm Port	Yes
USB Data Download Port	Optional
RS485 Port	Optional
Temperature Datalogger	Optional
Package	Plywood box with pallet
Shipping Weight	87 kgs
Shipping Size (WxDxH) mm	700x590x1210
Shipping Volume	0.5 CBM
Alt Name	22°C Platelet Shaking Incubator



FEATURES

Accurate microprocessor controller makes the inside temperature within $+22\pm 2^{\circ}\text{C}$ and resolution 0.1°C .

Suggested ambient temperature: $+10\sim 32^{\circ}\text{C}$.

Stainless steel inner chamber and shelves for friendly use and easy cleaning.

Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.

Toughened glass door with self-close function.

Wide available voltage range: $220\text{V}\pm 10\%$.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to power the controller and save temp. data when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Special designed service-free drainage system, ensure no water in the cabinet.

4 casters with stopper for easy moving and fixation.

UV sterilization: adjustable sterilization time and auto on/off when the door is closed/opened.

APPLICATIONS

The $+22^{\circ}\text{C}$ blood platelet shaking incubators are specially designed to store platelet for hospitals and blood stations.

PLATELET INCUBATOR BEZ1BE1

22°C PLATELET SHAKING INCUBATOR



An accurate microprocessor controller makes the inside temperature within $+22\pm 2^{\circ}\text{C}$ and resolution 0.1°C .
Suggested ambient temperature: $+10\sim 32^{\circ}\text{C}$.
Stainless steel inner chamber and shelves for friendly use and easy cleaning.
Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.
Toughened glass door with self-close function.
Wide available voltage range: $220\text{V}\pm 10\%$.
Security
Safety door lock and controller password to prevent unauthorized access.
Built-in backup battery to power the controller and save temp. data when power failure or system error.

SPECIFICATIONS

Model	BEZ1BE1
Old Model	BINC-702
Temperature Range	$20 \sim 24^{\circ}\text{C}$
Ambient Temperature	$10\sim 32^{\circ}\text{C}$
Capacity (L / Cu. Ft.)	158 / 5.58
Interior Dimensions (WxDxH) mm	432x462x728
Exterior Dimensions (WxDxH) mm	522x600x1285
Weight	85 kgs
Noise	50 dB
Oscillation Range	50 mm
Oscillation Frequency	60 times/min
Max Loading of 450ml Blood Bag	20 Bags
Controller	Microprocessor
Display	LCD
Sensor	NTC
Voltage and Frequency	$220\text{V}\pm 10\%$, 50/60Hz
Power	280 W
Electric Current	1.5 A
Power Consumption (kWh/24h)	4.4
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 72h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration Type	Forced-air Cooling
Defrost	Auto
Compressor (Brand/pcs)	EMBRACO / 1
Refrigerant / Weight (kgs)	R134a / 53g
Door (pcs)	Self-closing Foamed Glass Door / 1
Drawer (pcs)	10
Interior Cabinet Material	Stainless Steel

Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (845mm)
Door Lock	Yes
LED Lamp	UV Lamp
Test Hole (pcs)	Optional
Castors (pcs)	4
Temperature Printer	Yes
Remote Alarm Port	Yes
USB Data Download Port	Optional
RS485 Port	Optional
Temperature Datalogger	Optional
Package	Plywood box with pallet
Shipping Weight	109 kgs
Shipping Size (WxDxH) mm	590x710x1450
Shipping Volume	0.61 CBM
Alt Name	22°C Platelet Shaking Incubator



FEATURES

An accurate microprocessor controller makes the inside temperature within $+22\pm 2^{\circ}\text{C}$ and resolution 0.1°C .

Suggested ambient temperature: $+10\sim 32^{\circ}\text{C}$.

Stainless steel inner chamber and shelves for friendly use and easy cleaning.

Specially designed forced-air cooling system, ensures frost-free cabinet and good temperature uniformity.

Toughened glass door with self-close function.

Wide available voltage range: $220\text{V}\pm 10\%$.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to power the controller and save temp. data when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Special designed service-free drainage system, ensure no water in the cabinet.

4 casters with stopper for easy moving and fixation.

UV sterilization: adjustable sterilization time and will turn off automatically when the door is open.

APPLICATIONS

The $+22^{\circ}\text{C}$ blood platelet shaking incubators are specially designed to store platelet for hospitals and blood stations.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com