



LABORATORY VERTICAL AUTOCLAVE BAVT-2902

LABORATORY VERTICAL AUTOCLAVE BAVT-2902

VERTICAL AUTOCLAVE



- Three times pre-vacuum
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- LED touch screen display
- Standard test interface
- Self-expanding seal
- With drying function
- With stainless steel bucket or basket
- With automatic protection function/over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning.
- Automatic water

SPECIFICATIONS

Model	BAVT-2902
Capacity	50 L
Power	3.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C~134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 400x505
Bucket dimension	Ø 380x430
Basket dimension	Ø 360x280x1
Outer dimension	630x500x1180
Packing size	800x600x1230
Net weight	118 Kg
Gross Weight	138 Kg
Alt Name	Vertical Steam Sterilizer

FEATURES

- Three times pre-vacuum
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- LED touch screen display
- Standard test interface
- Self-expanding seal
- With drying function
- With stainless steel bucket or basket
- With automatic protection function/over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning.
- Automatic water

External steam Generator

Buzzer reminder after sterilization, automatic stop.

Automatic discharge of cold air, automatic steam exhaust after sterilization

Internal printer



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com