



LABORATORY VERTICAL AUTOCLAVE BAVT-502-A

LABORATORY VERTICAL AUTOCLAVE BAVT-502-A

VERTICAL AUTOCLAVE



1. Simple and easily understandable control panel to show the sterilization temperature, sterilization time, drying time, press separate keys to set the temperature and time makes the operation easier
2. Each sterilization stage is displayed with LED lights, making the sterilization process clear at a glance.
3. Microcomputer intelligent control system, achieves fully automatic control of the sterilization process.
4. The system automatically monitors the discharge of cold air to ensure a pure steam sterilization environment and the best sterilization effect.
5. Up to 20 error information records can be stored, facilitating instrument management.

Safety

SPECIFICATIONS

Model	BAVT-502-A
Capacity(L)	50
Dimension(L*W*H)(mm)	580x490x1085
Chamber dimension(Dia*H)(mm)	Φ 320 x 725
Power requirements	220V ± 10% 6A50HZ / 60HZ
Rated power(W)	2600W
Sus304 basket size(pcs)	(Φ 298 x 195) x 3
Chamber material	SUS304 stainless steel
Sterilization temperature	105°C~135°C
Sterilization time range	1~300min
Pressure gauge range	-0.1MPa~0.5MPa
Pulse times	0~9 times
Exhaust temperature range	73°C~104°C(SE/SR only, liquid mode)
Safety valve set pressure	0.29MPa
Drying	Drying temperature: 80°C~160°C
Sterilization	Sterilization + drying
Controller	Microcomputer control system
Safety device	Lid closing checking, over temperature protection system, dry scorch protection, over pressure protection, safety valve, over current/short circuit/electric leakage protection, scald protection, automatic failure-inspection system
Packing Dimension	73*63*125
CBM	0.57
Net Weight	105
Gross weight	126
Alt Name	Drying

ACCESSORIES FOR PURCHASE

No	Name	Description
----	------	-------------

1	Micro printer	To print temp.,time and FO value Printing set:printer+digital pressure sensor:can print temp. and pressure in data and flow chart way
2	Stainless steel bucket	
3	Digital pressure sensor	Printing set:printer+digital pressure sensor:can print temp. and pressure in data and flow chart way
4	1Q/0Q/PQ (3Q)adapter joint	
5	Tray	
6	Adjust foot	



1



2



3



4



5



6

FEATURES

- 1.Simple and easily understandable control panel to show the sterilization temperature, sterilization time, drying time, press separate keys to set the temperature and time makes the operation easier
2. Each sterilization stage is displayed with LED lights, making the sterilization process clear at a glance.
- 3.Microcomputer intelligent control system ,achieves fully automatic control of the sterilization process.
4. The system automatically monitors the discharge of cold air to ensure a pure steam sterilization environment and the best sterilization effect.
- 5.Up to 20 error information records can be stored, facilitating instrument management.

Safety



1. Lid closing checking:
Machine can not start if lid is not locking well,the self-induction interlock device can avoid risk of misuse
2. Unique anti-scald cover:
Nice look and avoid causing scald
3. Triple protection for lack of water:
The bottom of the sterilization chamber is equipped with three different dry burning protection devices: liquid expansion type, copper temperature sensing type, and electric ion type (water level sensor), to avoid misjudgment caused by a single method.
4. Double protection for over pressure:
Mechanical pressure gauge and electric sensing system, once pressure is abnormal, the system will cut power, release the pressure and send out an alarm.
5. Auto troubleshooting:
The system will monitor the working status, and will cut the power,send out an alarm, and report the error information once any abnormal situation is detected.
6. Safety test function: Regular testing of system security and safety protection measures is Possible
7. Real time monitor:
The system will monitor the lid locking, pressure and temperature status on a real time basis to guarantee the safe and successful work of the autoclave.

8. Electrical Protection:

Equipped with a highly sensitive electrical protection system, effectively providing leakage protection, overcurrent and short-circuit protection

Note:FD-SA has liquid mode, but can not preset the exhaust temperature for liquid mode.

MORE INFO

1. Pulse method to completely purge out cold air.
2. Fully automatic drying function or semi-automatic drying function choice
3. Fully automatic drying: Equipped with an air pump and a 0.2um air filter, it automatically starts drying after sterilization. After sterilization, clean air will be put in to replace the wet air inside, so as to improve drying efficiency.
4. Built in a water tank for internal discharging of steam, effectively absorbing water vapor from the exhaust process.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com