



BLOOD BANK REFRIGERATED CENTRIFUGE BBRC-204

BLOOD BANK REFRIGERATED CENTRIFUGE BBRC-204

FLOOR-STANDING HIGH-CAPACITY REFRIGERATED CENTRIFUGE



The max speed is 8000rpm, and the largest capacity of swing rotor is 6x2400ml. It has micro-computer control, electronic lock and AC variable-conversion motor which delivers high torque. Imported compressor unit with Non-CFC refrigerant R404a. It has self-locking, over-speed detection, over-temperature detection, imbalance detection that is an automatic alarm device. 9 levels acceleration and 9 levels deceleration. Silastic sealed ring comfort to GMP, US FDA certified.

SPECIFICATIONS

Model	BBRC-204
Max speed	8000 r/min
Max RCF	11260 xg
Max capacity	6x2400 ml
Speed accuracy	±10 r/min
Time setting	1s~99h 59min59s
Temperature setting	-20°C ~ +40°C
Temperature accuracy	±1°C
Compressor unit	French Tecumseh Compressor Unit R404a
Noise	<70 dB(A)
Power supply	AC380V 50Hz 40A
Consumption	7.5 kW
Alt Name	Floor-standing High-Capacity Refrigerated Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Rotor	Capacity: 6x500ml Max Speed: 8000r/min Max RCF: 11260xg Adaptor: 50ml, 100ml, 250ml
2	Swing Rotor	Capacity: 6x2000ml Max Speed: 4000r/min Max RCF: 6260xg
3	Adapter	2000ml Steel Bucket
4	Adapter	316L SS Bucket
5	Adapter	2000ml PP Bottle
6	Swing Rotor	Capacity: 6x2x1000ml Max Speed: 4000r/min Max RCF: 6260xg
7	Adapter	2x1000ml Steel Bucket
8	Swing Rotor	Capacity: 6x2400ml Max Speed: 4500r/min Max RCF: 6950xg

9	Adapter	2400ml Oval Steel Bucket
10	Adapter	2400ml Oval Bottle
11	Adapter	Individual Adaptor
12	Adapter	Interlayer Adaptor



1



2



3



4



5



6



7



8



9



10



11



12



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com