



LABORATORY HIGH SPEED CENTRIFUGE BCBH-103

LABORATORY HIGH SPEED CENTRIFUGE BCBH-103

TABLETOP HIGH-SPEED CENTRIFUGE



It has micro-computer control, electronic lock and DC brushless motor which is low noise and high speed accuracy.

Digital LCD screen make visualized operation conveniently.

Up to 9 user programs storage meet more demands.

It has self-locking, over-speed detection, over-temperature detection, imbalance detection that is automatic alarm device.

It has 9 levels acceleration and 10 levels deceleration to be setting according to the different requirement. Slow down freely is available.

Silastic sealed ring comfort to GMP, US FDA certificated.

SPECIFICATIONS

Model	BCBH-103
Max speed	16500r/min
Max RCF	23669xg
Max capacity	4x100ml
Speed accuracy	±30r/min
Time setting	1s~99min59s
Noise	<65dB (A)
Power supply	AC110V/AC220V, 50Hz~60Hz
Consumption	750W
Dimension (LxWxH)	330mmx420mmx280mm
Packing size (LxWxH)	430mmx520mmx390mm
Net weight (No rotor)	20kg
Alt Name	Tabletop High-Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Angle rotor	Capacity: 12x1.5 ml / 2.2 ml Max Speed: 16500 r/min Max RCF: 18930 xg Adaptor: 0.2 ml, 0.5 ml
2	Angle rotor	Capacity: 10x5 ml Max Speed: 13000 r/min Max RCF: 11400 xg Adaptor: 0.5 ml, 1.5 ml
3	Angle rotor	Capacity: 12x5 ml Max Speed: 13000 r/min Max RCF: 11400 xg Adaptor: 0.5 ml, 1.5 ml
4	Angle rotor	Capacity: 12x10 ml Max Speed: 12000 r/min Max RCF: 14800 xg Adaptor: 1.5 ml, 5 ml
5	Angle rotor	Capacity: 8x15 ml Max Speed: 12000 r/min Max RCF: 14800 xg Adaptor: 1.5 ml, 5 ml

6	Angle rotor	Capacity: 6x50 ml Max Speed: 11000 r/min Max RCF: 13000 xg Adaptor: 15 ml, 20 ml
7	Angle rotor	Capacity: 4x100 ml Max Speed: 10000 r/min Max RCF: 11750 xg Adaptor: 10 ml, 20 ml
8	Swing rotor	Capacity: 4x10 ml Max Speed: 6000 r/min Max RCF: 3200 xg
9	Microplate rotor	Capacity: 2x48 Max Speed: 3000 r/min Max RCF: 1400 xg
10	Angle rotor	Capacity: 24x1.5 ml / 2.2 ml Max Speed: 13200 r/min Max RCF: 16110 xg Adaptor: 0.2 ml, 0.5 ml
11	Angle rotor	Capacity: 36x0.5 ml Max Speed: 16000 r/min Max RCF: 23689 xg
12	Angle rotor	Capacity: 48x0.5 ml Max Speed: 16000 r/min Max RCF: 23689 xg
13	Angle rotor	Capacity: PCR 3x8x0.2 ml Max Speed: 15000 r/min Max RCF: 13800 xg
14	Angle rotor	Capacity: 48x1.5 ml Max Speed: 12000 r/min Max RCF: 15696 xg Adaptor: 0.2 ml, 0.5 ml



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com