



**LABORATORY HIGH SPEED REFRIGERATED
CENTRIFUGE BCBHR-309**

LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE

BCBHR-309

FLOOR STANDING HIGH SPEED LARGE CAPACITY REFRIGERATED CENTRIFUGE



SPECIFICATIONS

Model	BCBHR-309
Swing-Bucket Rotors	
--Max. Capacity	4 x 250 ml
--Max. Speed	4 500 rpm with 4 x 250 ml rotor
--Max. RCF	3 720 Xg with 4 x 250 ml rotor
Fixed-Angle Rotors	
Control System	Microprocessor via user-intuitive touchscreen interface control
Refrigeration System	CFC-Free
Drive System	Direct, induction motor drive (Inverter Control)
Display	Full color touchscreen interface
Rotor Identification	Auto-ID Instant, immediately upon rotor insertion
Programmability	via easy access touchscreen menu
Program Storage	1 000 user-defined
Running Time	1s - 99h:59min:59s, Short
Timer	Count up or down
Speed Accuracy	± 10 r/min
Accel/Decel Profiles	40/40
Temp. Control Range	-20 °C to +40 °C
Temp. Accuracy	± 1 °C
Noise Level	≤ 60 dB(A)
Power Supply	AC 200-240 V, 50/60 Hz or AC 100-127 V, 50/60 Hz
Max. Power Consumption	1.8 KW
Safety Device	Rotor identification system with overspeed protection, imbalance protection, overcurrent protection, lid interlock system, lid open/close detection, steel housing, corrosion-resistant stainless steel centrifuge chamber, additional inner steel armored guard ring, steel lid, etc.
Dimension (W x D x H)	26.8 x 24.4 x 33 in / 68 x 62 x 84 cm
Weight w/o Rotor	353 lb / 160 kg
Alt Name	Floor Standing High Speed Large Capacity Refrigerated Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Rotor Capacity (places x volume, ml)	Tube Size (Φ x L in mm)	Max Speed (rpm)	Max RCF (g)
1	No. 1 Fixed-Angle Rotor	12 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ 11 x 42	18 000 rpm	22 640 Xg
2	No. 2 Fixed-Angle Rotor	12 x 5 ml	Φ 14 x 54	18 000 rpm	20 780 Xg
3	No. 3-1 Fixed-Angle Rotor	24 x 1.5/2.0 ml	Φ 11 x 42	18 000 rpm	24 790 Xg
4	No. 3-2 Fixed-Angle Rotor	24 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ 11 x 42	18 000 rpm	31 370 Xg
5	No. 4-1 Fixed-Angle Rotor	12 x 10 ml	Φ 16 x 86	15 000 rpm	20 800 Xg
6	No. 4-2 Fixed-Angle Rotor	36 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ 11 x 42	15 000 rpm	20 800 Xg
7	No. 5-1 Fixed-Angle Rotor	6 x 50 ml (conical) a)	Φ 29 x 116	13 000 rpm	22 470 Xg
8	No. 5-2 Fixed-Angle Rotor	48 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ 11 x 42	13 000 rpm	18 420 Xg
9	No. 5-3 Fixed-Angle Rotor	6 x 50 ml (round) a)	Φ 29 x 111	13 000 rpm	22 470 Xg
10	No. 6-1 Fixed-Angle Rotor	4 x 100 ml	Φ 38 x 123	10 000 rpm	11 040 Xg
11	No. 6-2 Fixed-Angle Rotor	8 x 50 ml (conical) a)	Φ 29 x 116	10 000 rpm	11 040 Xg
12	No. 6-3 Fixed-Angle Rotor	12 x 15 ml	Φ 17 x 121	12 000 rpm	15 890 Xg
13	No. 6-4 Fixed-Angle Rotor	8 x 50 ml (round) a)	Φ 29 x 111	10 000 rpm	11 040 Xg
14	No. 6-5 Fixed-Angle Rotor	24 x 10 ml	Φ 16 x 86	10 000 rpm	11 040 Xg
15	No. 7 Fixed-Angle Rotor	6 x 10 ml	Φ 16 x 86	16 000 rpm	18 980 Xg
16	No. 8-1 Fixed-Angle Rotor	8 x 15 ml a)	Φ 17 x 121	14 000 rpm	17 310 Xg
17	No. 8-2 Fixed-Angle Rotor	6 x 30 ml	Φ 25.5 x 100	14 000 rpm	17 310 Xg
18	No. 9 Swing-Bucket Rotor	2 x 3 pcs microplates (96 wells) or 2 x 3 pcs microtiter plates or 2 x 2 pcs cell culture plates or 2 x 1 pc deep well plates	Load dimensions (WxDxH) up to 128x87x60 mm	4 000 rpm	1 970 Xg
19	Rotor Cross (order buckets, adapters separately)	-	-	-	-
20	No. 10 Swing-Bucket 250 ml Round Buckets (set of 4)	4 x 250 ml	Φ 63 x 111	-	-
21		4 x 100 ml	Φ 38 x 114	-	-
22	(Adapters for 250 ml Round Buckets, sets of 4 for each)	4 x 50 ml	Φ 29 x 111-116	4 500 rpm	3 720 Xg
23		8 x 50 ml (conical)	Φ 29 x 116		
24		8 x 50 ml (round)	Φ 29 x 111		
25		8 x 30 ml	Φ 25.5 x 100		
26		20 x 15 ml	Φ 16.5 x 111		

27		36 x 10 ml	Φ16.5 x 86-110		
28		20 x 5 ml (conical)	Φ17 x 60		
29		32 x 1.5/2.0 ml	Φ11 x 42		
30		32 x 2.0 ml	Φ10.8 x 44		
31		40 x 0.5 ml	Φ8 x 30		
32		20 x 10 ml virus sampling tube	Φ16 x 97-101		
33		28 x 4-10 ml blood collection/urine tube	Φ16 x 75-100/Φ15 x 75-102		
34		40 x 1.6-7 ml blood collection/urine tube	Φ13 x 75-100		
35		148 x 5 ml Radio-immunity tube	Φ13 x 75-100		
36	Conical Buckets (set of 4)	4 x 175/225 ml Falcon conical bottle	Φ61 x 118/137	4 000 rpm	3 100 Xg
37	Buckets (set of 4)	36 x 4-10 ml blood collection/urine tube	Φ16 x 75-100/Φ15 x 75-102		
38	Buckets (set of 4)	48 x 1.6-7 ml blood collection/urine tube	Φ13 x 75-100		
39	Buckets (set of 4)	64 x 1.6-7 ml blood collection/urine tube	Φ13 x 75-100		
40	No. 11 Fixed-Angle Rotor	12 x 50 ml (conical) a)	Φ29 x 116	10 000 rpm	14 310 Xg



1



2



3



4



7



20



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com