



LABORATORY LOW SPEED CENTRIFUGE BCBL-302



LABORATORY LOW SPEED CENTRIFUGE BCBL-302

TABLETOP LOW SPEED CENTRIFUGE



1. Widely used in hospital, laboratory and blood bank.
2. Brushless DC motor for model which in great torque, free maintenance, no powder pollution, quick in speed up and down.
3. The flexible axle driven system which drive the rotor directly, smooth in operation, low noise and small vibration.
4. Micro computer control system, digital display in the RCF,time and speed.
5. Electric lid lock, compact design, super speed and imbalance protection.
6. The centrifuge body is made of high-quality steel, safe and reliable.

SPECIFICATIONS

Model	BCBL-302
Max. Speed	4000rpm
Max. RCF	2250xg
Max. Capacity	6x50ml
Time Range	0~99min59sec
Noise	≤ 45dBA
Speed Accuracy	±10rpm
Size (W x D x Hmm)	265x483x320mm
Net Weight(Kg)	20KG
Power supply	AC 220V 50HZ 2A
Temperature Range	-20~40°C
Package	Carton box
Alt Name	Tabletop low speed centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Max Speed (rpm)	Max Volume (ml)	Max RCF (g)
1	Angle Rotor	4000	30x7/5ml	2250
2	Angle Rotor	4000	18x10ml	2250
3	Angle Rotor	4000	24x10ml	2200
4	Angle Rotor	4000	12x15/7/5ml	2150
5	Angle Rotor	4000	12x20ml	2220
6	Angle Rotor	4000	6x50ml	2100



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com