



LABORATORY LOW SPEED CENTRIFUGE BCBL-303

LABORATORY LOW SPEED CENTRIFUGE BCBL-303

TABLETOP LOW SPEED CENTRIFUGE



1. Widely used in hospital, laboratory.
2. Brushless DC motor for model which in great torque, free maintenance, no powder pollution, quick in speed up and down.
3. The flexible axle driven system which drive the rotor directly, smooth in operation, low noise.
4. Micro computer control system, digital display in the RCF,time and speed.
5. Electric lid lock, compact design, super speed and imbalance protection.
6. The centrifuge body is made of high-quality steel, safe and reliable.

SPECIFICATIONS

Model	BCBL-303
Max. Speed	6000rpm
Max. RCF	4730xg
Max. Volume	4x250ml
Time Range	0~99min
Noise	≤ 58dBA
Speed Accuracy	±20rpm
Temperature accuracy	±1°C
Size (W x D x Hmm)	265x483x320mm
Net Weight(Kg)	23KG
Power supply	AC 220V 50HZ 2A
Temperature range	-20~40°C
Package	Carton box
Alt Name	Tabletop Low Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Max Speed (rpm)	Max Volume (ml)	Max RCF (g)
1	Angle Rotor	6000	6x10/7/5ml	3450
2	Angle Rotor	6000	6x15/7/5ml	3660
3	Angle Rotor	4000	24x10ml	2200
4	Angle Rotor	5000	12x15/7/5ml	3080
5	Angle Rotor	4000	12x20ml	2220
6	Angle Rotor	4000	6x50ml	2100



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com