



LABORATORY LOW SPEED CENTRIFUGE BCBL-304



LABORATORY LOW SPEED CENTRIFUGE BCBL-304

TABLETOP LOW SPEED CENTRIFUGE



1. Microprocessor control, less noisily, it is widely used to qualitative analysis of blood serum, plasma and urea in the fields of hospital, blood center, laboratory and biochemistry.
2. Brushless motor, free maintenance, no powder pollution, quick in speed up and down.
3. The flexible axle driven system which drive the rotor directly, smooth in operation and small vibration.
4. There are many rotors for your choice, suitable for different specifications meet customers' different requirements of separation.
5. Micro computer control system, LED display the RCF,time and speed.
6. Electric lid lock, compact design, super speed and imbalance protection.

SPECIFICATIONS

Model	BCBL-304
Max. Speed	5000rpm
Max. RCF	4420xg
Max. Capacity	6x100ml
Time Range	0~99min59sec
Noise	≤ 55dBA
Speed Accuracy	± 20r/min
Voltage(V/Hz)	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	540x370x280mm
Net Weight(Kg)	32KG
Certificates	CE,ISO & Calibration report are available
Alt Name	Tabletop Low Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Max Speed (rpm)	Max Volume (ml)	Max. RCF (xg)
1	Swing out rotor	4000	4x50ml/100ml	2250
2	Swing out rotor	4000	16x15ml	2150
3	Swing out rotor	4000	24x10ml	2220
4	Angle rotor	4000	18x10ml	2250



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com