

LABORATORY LOW SPEED CENTRIFUGE BCBL-305

CELL WASHER/SEROFUGE CENTRIFUGE



1. Microprocessor control, less noisily, it is widely used to qualitative analysis of blood serum, plasma and urea in the fields of hospital, laboratory and biochemistry.
2. Brushless motor, free maintenance, no powder pollution, quick in speed up and down.
3. Special program, HLA and SERO separately.
4. Micro computer control system, LED display the RCF, time and speed.
5. Electric lid lock, compact design, super speed and imbalance protection.

SPECIFICATIONS

Model	BCBL-305
Max. Speed	4000rpm
Max. RCF	2000
Max. Capacity	12x7
Time Range	0~99min59sec
RPM/RCF Convert	Yes
Noise (dB)	≤ 55
Temperature	Normal
Acc/Dec	10 Kinds
Speed Accuracy	± 20r/min
Voltage(V/Hz)	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	485x320x255mm
Net Weight(Kg)	20KG
Alt Name	Cell Washer/Serofuge Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Max Speed (rpm)	Max Volume (ml)	Max. RCF (xg)
1	SERO Rotor	3000	12x7/5ml(10-13 *65-100mm)	1000
2	HLA Rotor	4000	12x2/1.5/0.5ml	2000



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com