



LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE BCBLR-309

LABORATORY HIGH SPEED REFRIGERATED CENTRIFUGE

BCBLR-309

BENCHTOP HIGH SPEED REFRIGERATED CENTRIFUGE



SPECIFICATIONS

Model	BCBLR-309
Max. Capacity	6 x 100 ml
Max. Speed	20 000 rpm with 12 x 1.5/2.0 ml
Max. RCF	31 370 Xg with 24 x 1.5/2.0 ml
Control System	Microprocessor
Refrigeration System	CFC-Free
Drive System	Direct, induction motor drive (Inverter Control)
Display	Full color touchscreen interface
Rotor Identification	Auto-ID Instant, immediately upon rotor insertion
Programmability	via easy access touchscreen menu
Program Storage	1 000 user-defined
Running Time	1 s - 99 h : 59 min : 59 s
Timer	Count up or down
Speed Accuracy	± 10 r/min
Accel/Decel Profiles	40/40
Temp. Control Range	-20 °C to +40 °C
Temp. Accuracy	± 1 °C
Noise Level	≤ 57 dB(A)
Power Supply	AC 200-240 V, 50/60 Hz or AC 100-127 V, 50/60 Hz
Max. Power Consumption	1.2 KW
Dimension (W x D x H)	16.5 x 20.5 x 14.2 in / 42 x 52 x 36 cm
Weight w/o Rotor	132 lb / 60 kg
Alt Name	Benchtop High Speed Refrigerated Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Rotor Capacity (places x volume, ml)	Tube Size (Φ x L in mm)	Max Speed (rpm)	Max RCF (g)
1	No.1 Fixed-Angle Rotor	12 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ11 x 42	20,000 rpm	27,950 Xg
2	No.2 Fixed-Angle Rotor	12 x 5 ml	Φ14 x 54	17,000 rpm	23,460 Xg
3	No.3-1 Fixed-Angle Rotor	24 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ11 x 42	16,000 rpm	24,790 Xg

4	No.3-2 Fixed-Angle Rotor	24 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ11 x 42	18,000 rpm	31,370 Xg
5	No.4-1 Fixed-Angle Rotor	12 x 10 ml	Φ16 x 86	15,000 rpm	21,200 Xg
6	No.4-2 Fixed-Angle Rotor	36 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ11 x 42	15,000 rpm	21,760 Xg
7	No.5-1 Fixed-Angle Rotor	6 x 50 ml (conical)	Φ29 x 116	12,500 rpm	17,030 Xg
8	No.5-2 Fixed-Angle Rotor	48 x 1.5/2.0 ml (with adapters for 0.2/0.5 ml tube)	Φ11 x 42	12,500 rpm	15,780 Xg
9	No.5-3 Fixed-Angle Rotor	6 x 50 ml (round)	Φ29 x 111	12,500 rpm	17,030 Xg
10	No.6-1 Fixed-Angle Rotor	4 x 100 ml	Φ38 x 123	11,000 rpm	13,350 Xg
11	No.6-2 Fixed-Angle Rotor	8 x 50 ml (conical)	Φ29 x 116	11,000 rpm	14,030 Xg
12	No.6-3 Fixed-Angle Rotor	12 x 15 ml	Φ17 x 121	11,000 rpm	12,870 Xg
13	No.6-4 Fixed-Angle Rotor	8 x 50 ml (round)	Φ29 x 111	11,000 rpm	13,350 Xg
14	No.6-5 Fixed-Angle Rotor	24 x 10 ml	Φ16 x 86	11,000 rpm	13,350 Xg
15	No.7 Fixed-Angle Rotor	6 x 10 ml	Φ16 x 86	16,000 rpm	18,980 Xg
16	No.8-1 Fixed-Angle Rotor	8 x 15 ml	Φ17 x 121	14,000 rpm	17,310 Xg
17	No.8-2 Fixed-Angle Rotor	6 x 30 ml	Φ25.5 x 100	14,000 rpm	18,450 Xg
18	No.9 Fixed-Angle Rotor	8 x PCR-Strips	-	13,000 rpm	14,640 Xg
19	No.10 Fixed-Angle Rotor	6 x 100 ml	Φ38 x 123	9,000 rpm	9,770 Xg
20	No.11 Fixed-Angle Rotor	24 x 2.0 ml Cryo tube	Φ11.5 x 45	15,000 rpm	23,400 Xg
21	No.12 Swing-Bucket Rotor	2 x 2 pcs microplates (48 wells)	Load dimensions (WxDxH) up to 128x48x60 mm	4,000 rpm	1,500 Xg



2



7



12



18



19



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com