



CLASS III BIOSAFETY CABINET BCBS-502

CLASS III BIOSAFETY CABINET BCBS-502

CLASS III BIOLOGICAL SAFETY CABINET



1. With memory function in case of power-failure.
 2. UV lamp ensures work area sterilization effectively.
 3. An angled cabinet front ensures an ergonomic working posture.
 4. Exhaust air is double-filtered through high-quality ULPA filters with typical efficiency of 99.9995% for 0.12um particles.
- Pass Box, Double doors with interlock function and UV lamp
 Pressure Meter, Display the pressure of work zone.
 UV Lamp, Emission of 253.7 nanometers for most efficient decontamination.
 LCD Display, Large display is easy to monitor the pressure parameters for work zone and three filters.

SPECIFICATIONS

Model	BCBS-502
External Size(W*D*H)	1790*880*2080 mm
Internal Size(W*D*H)	1165*650*660 mm
Pass Box Size(W*D*H)	Internal Size:430*330*355mm External Size:575*425*495mm
Gloves	One pair of 800mm butyl rubber gloves
Front Window	8 mm toughened glass, anti-ultraviolet radiation
Display	LCD display
Pre-Filter	Polyester fiber, washable
Pressure	Negative, ≥120 Pa
ULPA Filter	Air supply filter: Efficiency 99.9995% at 0.12µm First exhaust filter: Efficiency 99.9995% at 0.12µm Second exhaust filter: Efficiency 99.9995% at 0.12µm
Noise	≤67dB
Alarm	Audio and visual alarm, abnormal pressure; filter replacement
Work Zone Material	304 stainless steel
Illumination	≤67dB
Consumption	1300W
LED Lamp	16W*2
UV Lamp	30W*2, 8W*1 Emission of 253.7 nanometers for most efficient decontamination
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz
Gross Weight	450kg
Package Size(W*D*H)	1890*1065*2250mm
Standard Accessories	Gloves, fluorescent lamp, UV lamp*3, remote control, pressure meter, drain valve
Alt Name	Class III Biological Safety Cabinet

FEATURES

1. With memory function in case of power-failure.
2. UV lamp ensures work area sterilization effectively.
3. An angled cabinet front ensures an ergonomic working posture.
4. Exhaust air is double-filtered through high-quality ULPA filters with typical efficiency of 99.9995% for 0.12um particles.


Pass Box, Double doors with interlock function and UV lamp



Pressure Meter, Display the pressure of work zone.



UV Lamp, Emission of 253.7 nanometers for most efficient decontamination.



LCD Display, Large display is easy to monitor the pressure parameters for work zone and three filters.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com