



LABORATORY LOW SPEED CENTRIFUGE BCFL-203



LABORATORY LOW SPEED CENTRIFUGE BCFL-203

CRUDE OIL TESTING CENTRIFUGE



1. Programmable microprocessor control system, big LCD display in rotor No., speed, time, temperature, RCF, rate of speed as well as fault information.
2. Adopts band heater, fast heating speed, temperature uniform, with the function of temperature-control and constant.
3. Centrifugal tube made in special skill, anti-broken when work.
4. Great torque brushless frequency motor, maintenance-free, no powder, fast acceleration and deceleration, low noise, which improve the stability a lot.
5. Electric lid lock, over-speed and over-temperature protection
6. 3 phase to keep the best performance.
7. Stainless steel chamber, safe and reliable

SPECIFICATIONS

Model	BCFL-203
Max. Speed	4000rpm
Max. RCF	3830xg
Max. Capacity	4x100ml
Time Range	0~99min59sec
Noise	≤ 60dBA
Speed Accuracy	± 20r/min
Size (W x D x Hmm)	685x500x405mm
Net Weight(Kg)	67KG
Temperature Range	Room temperature +10~80°C
Package	Wooden box
Alt Name	Crude Oil Testing Centrifuge



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com