



LABORATORY LOW SPEED CENTRIFUGE BCFL-302-B

LABORATORY LOW SPEED CENTRIFUGE BCFL-302-B

LOW SPEED CENTRIFUGE



1. Microprocessor control, digital display, touch panel, parameters in running can be edited and change to display other running parameter and RCF.
2. Brushless frequency motor with simpler construction, more reliable performance, longer life and quietly running.
3. super speed, over temperature protection and imbalance protection. The centrifuge body is made of high quality steel, safe and reliable.
4. Adapters are available by experiment requirements.
5. 3 tiers protection steel cover, safe and reliable.

SPECIFICATIONS

Model	BCFL-302-B
Max. Speed	6000rpm
Max. RCF	3660xg
Max. Capacity	6x100ml
Time Range	0~99min59sec
RPM/RCF Convert	Yes
Noise	≤ 55dBA
Speed Accuracy	±20rpm
Acc/Dec	10 Kinds
Temperature range	Normal
Power supply	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	485x320x255mm
Net Weight(Kg)	18KG
Certificates	CE,ISO & Calibration report are available
Alt Name	Low Speed Centrifuge

ACCESSORIES FOR PURCHASE

No	Name	Max Speed (rpm)	Max Volume (ml)	Max. RCF (xg)
1	Angle Rotor	6000	6x15ml/10ml/7ml/5ml	3660
2	Angle Rotor	5000	12x15ml/10ml/7ml/5ml	3080
3	Angle Rotor	5000	6x50ml	2850
4	Angle Rotor	6000	4x50ml	3620
5	Angle Rotor	6000	4x100ml	3790
6	Angle Rotor	5000	6x100ml	3130
7	Swing rotor	5000	6x10ml	3460



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com