



PRODUCT CATALOG



LABORATORY LOW SPEED REFRIGERATED CENTRIFUGE BCFL-303

LABORATORY LOW SPEED REFRIGERATED CENTRIFUGE

BCFL-303

TABLE TOP LOW SPEED REFRIGERATED CENTRIFUGE



SPECIFICATIONS

Model	BCFL-303
Max. Speed	6000rpm
Max. RCF	3660xg
Max. Capacity	4x180ml
Time Range	1~99min59sec
RPM/RCF Convert	Yes
Noise	≤ 58dBA
Speed Accuracy	±20rpm
Acc/Dec	10 Kinds
Temperature range	-20°C-40°C
Temperature Accuracy	±1°C
Power supply	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	520x520x285mm
Net Weight(Kg)	48KG
Certificates	CE,ISO & Calibration report are available
Alt Name	Table Top Low Speed refrigerated centrifuge



ACCESSORIES FOR PURCHASE

No	Name	Max speed (rpm)	Max Volume (ml)	Max RCF (g)
1	Angle rotor	6000	6x15ml	3660
2	Angle Rotor	6000	4x50ml	3628
3	Angle Rotor	6000	4x100ml	3790
4	Angle Rotor	5000	12x15ml	3080
5	Angle Rotor	5000	6x50ml	2850
6	Angle Rotor	5000	6x100ml	3130
7	Swing Rotor	5000	6x10ml	3460
8	Swing Rotor	4000	16x5ml/7ml	2200



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com