



CHROMATOGRAPHY BCHR-108

CHROMATOGRAPHY BCHR-108

GAS CHROMATOGRAPHY



The host uses a 7-inch color touch screen, electronic display gas flow and pressure values.

Computer anti-control (need to choose PC-side anti-control software) and the host touch screen to achieve synchronous two-way control.

Multi-core, 32-bit embedded hardware system to ensure reliable operation of the instrument.

One key to start a function.

Extensible synchronous external triggering function can be initiated by external signals (autosampler, thermal analyzer, etc.) at the same time to start the host and workstation.

Has a perfect system self-test function and automatic fault recognition.

Extended interface with 8 external events, which can be equipped with various fu

SPECIFICATIONS

Model	BCHR-108
Column Oven	
- Inner volume	22L
- Temperature range	5°C - 400°C at room temperature
- Temperature control accuracy	±0.1°C
- Heating rate	0.1 - 60°C / min
- The order of heating of the program	9
- Program temperature repeatability	≤2%
- Cooling method	after the door
- Cooling rate	≤10 mins (250°C - 50°C)
Sampler	
- Temperature control range	room temperature 7°C - 420°C
- Temperature control mode	independent temperature control
- Carrier gas flow control mode	constant pressure
- Number of simultaneous installations	up to 3
- Injection unit type	packed column, shunt
- Split ratio	display
- Pre column pressure range	0 - 400 kPa
- Pre column pressure control accuracy	Pre column pressure control accuracy: 0.1 kPa
- Flow setting range	H2O-200 ml/min, N2O-150 ml/min
- FID, TCD	optional one
Detector	
- Ignition function	automatic
- Detector	Hydrogen flame ionization detector (FID)
- Detection limit:	≤3×10 ⁻¹² g/s (n-hexadecane)
- Baseline noise	≤5×10 ⁻¹⁴ A
- Baseline drift	≤6×10 ⁻¹³ A
- Dynamic range	10 ⁷
- RSD	≤3%
- Sensitivity	5000 mV·ml/mg (n-hexadecane)
Thermal Conductivity Detector (TCD)	
- Power supply voltage	220V ±22V, 50Hz ±0.5Hz
Power	Power: 3000W

FEATURES

The host uses a 7-inch color touch screen, electronic display gas flow and pressure values.

Computer anti-control (need to choose PC-side anti-control software) and the host touch screen to achieve synchronous two-way control.

Multi-core, 32-bit embedded hardware system to ensure reliable operation of the instrument.

One key to start a function.

Extensible synchronous external triggering function can be initiated by external signals (autosampler, thermal analyzer, etc.) at the same time to start the host and workstation.

Has a perfect system self-test function and automatic fault recognition.

Extended interface with 8 external events, which can be equipped with various function control valves and operate according to their own timing.

20 sets of sample test mode memory functions.

RS232 communication port.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com