



## BACTERIAL COLONY COUNTER BCLC-103

# BACTERIAL COLONY COUNTER BCLC-103

## MICROBIAL COLONY SPREADER



1. Four speeds options for user's requirement:200RPM,250RPM,300RPM,350RPM
2. Aluminum alloy disc can be sterilized by disinfectants and UV;
3. Continuous operation is for daily use;
4. Feasible 70/90mm plate, no need to replace the adapter

## SPECIFICATIONS

|                           |                                   |
|---------------------------|-----------------------------------|
| Model                     | BCLC-103                          |
| Main power supply voltage | Voltage: ~220 V; Frequency: 50 Hz |
| Current                   | 0.5 A                             |
| Diameter                  | 170 mm (6.7 inches)               |
| Height                    | 80 mm (3.15 inches)               |
| Weight                    | 1.2 kg (2.6 lbs.)                 |
| Running Temperature       | 15 °C to 30 °C (59 °F to 95 °F)   |
| Storage Temperature       | -20 °C to 55 °C (-4 °F to 135 °F) |
| Relative Humidity         | 31 °C, ≤ 80%                      |
| Altitude                  | ≤ 2000 m                          |
| Pollution Level           | 2                                 |
| Voltage Classification    | II                                |
| Alt Name                  | Microbial Colony Spreader         |

## ITEMS INCLUDED

| No | Name            |
|----|-----------------|
| 1  | Micro-Rot Alpha |



1



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)