



CONCENTRATOR BCON-105

CONCENTRATOR BCON-105

WATER BATH CONCENTRATOR

Water Bath Sample Concentrator is mainly used for the concentration or preparation of large quantities of samples (such as drug screening, hormone analysis, liquid phase, and sample preparation in mass spectrometry analysis). Working principle: By blowing nitrogen into the surface of the heated sample, the solvent in the sample is quickly evaporated and separated, so as to achieve the purpose of oxygen-free concentration of the sample and keep the sample more pure.



Elegant appearance, with elevation operation panel, embedded flowmeter, waterproof button, safe and reliable.
Good compatibility, suitable for test tubes (diameter 10 ~ 29mm), conical flask, centrifuge tube, the sample capacity of 1 ~ 50ml.
Free up and down needle valve tube, independent adjustable needle valve, controls gas flow at each sample location
Circular turntable structure, 360-degree rotation, convenient sample support into and out of the water bath, easy to operate.
12 position, each sample position are numbered, spring tube clamp fixed position.
LED real-time displays temperature and time, water bath temperature: RT +5 °C ~ 100 °C.

SPECIFICATIONS

Model	BCON-105
Temp. Control Range	R.T.+5°C~100°C
Temp. Setting Range	5°C~100°C
Temp. Uniformity@60°C	±1 °C
Temp. Display Accuracy	0.1 °C
Heating Speed	<30min (40°C to 100°C)
Time Range	1min~99h59min
Accommodates samples	12
Test tube range	Φ10~29mm/ Liquid volume1~50ml
Needle Plate Max. Lift Stroke	200mm
as-in Joint Outer Diameter	Φ7mm
Maximum gas pressure	0.2MPa
Maximum gas flow	15L/min
Needle Length	100mm
Inner dimension	Φ260x150mm
Voltage	AC 220V, 50/60Hz
Power	1000W
Fuse	250V, 8A, Φ5x20
Dimensions	W.390 x D.300 xH.850mm
Net Weight	9.5kgs
Alt Name	Water Bath Concentrator

FEATURES

Elegant appearance, with elevation operation panel, embedded flowmeter, waterproof button, safe and reliable.
Good compatibility, suitable for test tubes (diameter 10 ~ 29mm), conical flask, centrifuge tube, the sample capacity of 1 ~ 50ml.
Free up and down needle valve tube, independent adjustable needle valve, controls gas flow at each sample location
Circular turntable structure, 360-degree rotation, convenient sample support into and out of the water bath, easy to operate.
12 position, each sample position are numbered, spring tube clamp fixed position.
LED real-time displays temperature and time, water bath temperature: RT +5 °C ~ 100 °C.

All use of stainless steel, all components are anti-corrosion and resistant to organic solvents.

When concentrated toxic solvents, the entire system can be placed in a fume hood.

Built-in level sensor, anti-dry protection.

Suitable for a variety of test tubes, so that the gas needle is aimed at the center of the test tube, and the experimental effect is greatly improved.

APPLICATIONS

Pharmaceutical drug testing: Chinese medicine and drug testing.

Food and beverage: milk, wine, liquid beverages.

Biological analysis: serum, plasma, blood, urine.

Commodity inspection: test dioxin, croft etc.

Environmental analysis: drinking water, groundwater, polluted water, etc.

Pesticide analysis: vegetables, fruits, cereals, plant tissues, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com