



ANIMAL CAGE CHANGING STATION BDL-6401

ANIMAL CAGE CHANGING STATION BDL-6401

ANIMAL CAGE CHANGING STATION


The animal cage changing station is suitable for the replacement of animal cages in SPF animal rooms, the anatomy of experimental animals and the separation of tissues, etc. It adopts positive vertical flow, double primary effect and double high efficiency filtration design, which can prevent animals in the work area from being polluted by outside air. Protect the operator from allergens and special odors generated during the experiment. In addition, the double-sided open design facilitates simultaneous operation by multiple person. It is a safety protection device specially designed for animal research laboratories.



1. Two-way safety protection: with excellent ventilation system and negative pressure airflow, it can provide two-way safety protection for people, animals, environment, and objects during the process of animal cage change.
 2. Use high-quality materials: the work surface is made of 304 stainless steel, which can be quickly disassembled and cleaned up waste.
 3. Double-layer filtration system: primary and high-efficiency double-layer filtration system.
 4. Control system: LCD touch screen design, real-time dynamic display of the airflow speed of the workstation.
 5. Audio and visual alarm: Abnormal air flow velocity and Filter replacement .
- V-type air grille: V-type air grid collects ambient air and combines with vertical laminar downflow to produce an air curtain to protect operators from harmful

SPECIFICATIONS

Model	BDL-6401
Power Supply	AC220V±10%, 50/60Hz(Standard) AC110V, 60Hz(Optional)
Instrument Size(L*D*H)	1580*750*1980mm
Operating Area Size(L*D*H)	1015*750*585mm
Laminar Airflow Velocity	≥0.35m/s
Noise	≤65dB(A)
Illuminance	≥1000lx
LED Lamp	12W*2
Consumption(W)	800W
Air Supply ULPA Filter Size	925*470*69mm
Exhaust ULPA Filter Size	910*480*69mm
Primary Filter Size	890*505*25mm
Filtration Efficiency	99.9995%(φ0.12μm)
Number of Users	1- 2
Package Size (L*D*H)	1460*890*2270mm
Gross Weight	243kg
Alt Name	Animal Cage Changing Station



- Primary Efficiency Filter
- ULPA Filter
- Room Air
- Polluted Air
- Semi-Purified Air
- Purified Air
- A Protected Area
- B Polluted Air
- C Semi- Polluted Air

FEATURES

1. Two-way safety protection: with excellent ventilation system and negative pressure airflow, it can provide two-way safety protection for people, animals, environment, and objects during the process of animal cage change.
2. Use high-quality materials: the work surface is made of 304 stainless steel, which can be quickly disassembled and cleaned up waste.
3. Double-layer filtration system: primary and high-efficiency double-layer filtration system.
4. Control system: LCD touch screen design, real-time dynamic display of the airflow speed of the workstation.
5. Audio and visual alarm: Abnormal air flow velocity and Filter replacement .

V-type air grille: V-type air grid collects ambient air and combines with vertical laminar downflow to produce an air curtain to protect operators from harmful substances.



Stainless steel tray: The left side of the workstation is equipped with a stainless steel tray for easy placement of experimental supplies.



Highlight LCD touch screen design: Real-time dynamic display of the downflow velocity and inflow velocity, the overall operating time, the temperature and humidity, and the resistance of the air supply and exhaust filters.



Easy to move: The Fuma caster design and the right side handle design, easy to move the cabinet



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com