



DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER BDL-6902

DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER

BDL-6902

DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER

The Double Adjustable Frequencies Type device is a versatile equipment commonly used in applications requiring precise frequency modulation for various industrial, medical, and research purposes.



1. Over-voltage and over-current protection.
2. Standard: 1pc of basket, 1pc of lid.
3. Low-level water protection.
4. Fully microprocessor controlled and programmable.
5. Digital display, easy setting for time and temperature.
6. Time and temperature real-time display.

SPECIFICATIONS

Model	BDL-6902
Capacity (L)	27
Adjustable Ultrasonic Frequency (KHz)	45/80
Time Range / Heating Temp	1~480min / 0~80°C
Ultrasonic Power (W)	500
Heating Power (W)	800
Tank Size (L*W*H mm)	500*300*180
Packing Size (L*W*H mm)	1100*690*800
Gross Weight (kg)	101
Standard Power Supply	AC220V±10%, 50/60Hz
Alt Name	Double Adjustable Frequencies Ultrasonic Cleaner



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com