



## MINI DRY BATH INCUBATOR BDMI-109

# MINI DRY BATH INCUBATOR BDMI-109

MINI-DRY BATH INCUBATOR



Small footprint: They are a personal size that fits in the palm on your hand; light weight, less than 1 kg.  
 DC 12V or DC 24V power input, built-in over temperature protection device, suitable for car power supply.  
 Temperature deflection adjusting meets with different demands.  
 Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting.

## SPECIFICATIONS

Model	BDMI-109
Temperature control range	RT. +5 °C~100 °C
Timer range	1-999 min or 1-999 sec
Temp. control accuracy	±0.5 °C
Display accuracy	±0.1 °C
Heating time (25 °C to max.)	≤15 min
Cooling time (20 °C to 0 °C)	/
Temp. stability	±0.3 °C
Thermo lid	/
Thermo lid temp. control range	/
Dimension (LxWxH) mm	152x120x112
Weight	0.8 kg
Power supply	DC 24 V
Alt Name	Mini-Dry Bath Incubator

## ACCESSORIES FOR PURCHASE

No	Name	Description
1	Block	40x0.2 mL tube
2	Block	24x0.5 mL tube
3	Block	15x1.5 mL tube
4	Block	15x2.0 mL tube
5	Block	8x12.5x12.5 mL cuvette block
6	Block	4x15 mL tube
7	Block	2x50 mL tube
8	Block	



1



2



3



4



5



6



7

## FEATURES

Small footprint: They are a personal size that fits in the palm on your hand; light weight, less than 1 kg.  
DC 12V or DC 24V power input, built-in over temperature protection device, suitable for car power supply.  
Temperature deflection adjusting meets with different demands.  
Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)