



MINI DRY BATH INCUBATOR BDMI-111

MINI DRY BATH INCUBATOR BDMI-111

MINI-DRY BATH INCUBATOR



Small footprint: They are a personal size that fits in the palm on your hand; light weight, less than 1 kg.
 DC 12V or DC 24V power input, built-in over temperature protection device, suitable for car power supply.
 Temperature deflection adjusting meets with different demands.
 Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting.

SPECIFICATIONS

Model	BDMI-111
Temperature control range	RT. +5 °C~100 °C
Timer range	1-999 min or 1-999 sec
Temp. control accuracy	±0.5 °C
Display accuracy	±0.1 °C
Heating time (25 °C to max.)	≤15 min
Cooling time (20 °C to 0 °C)	/
Temp. stability	±0.3 °C
Thermo lid	Thermo lid
Thermo lid temp. control range	RT. +5 °C~100 °C
Dimension (LxWxH) mm	152x120x112
Weight	0.9 kg
Power supply	DC 24 V
Alt Name	Mini-Dry Bath Incubator

ACCESSORIES FOR PURCHASE

No	Name	Description
1	Block	40x0.2 mL tube
2	Block	24x0.5 mL tube
3	Block	15x1.5 mL tube
4	Block	15x2.0 mL tube
5	Block	8x12.5x12.5 mL cuvette block
6	Block	4x15 mL tube
7	Block	2x50 mL tube
8	Block	



1



2



3



4



5



6



7

FEATURES

Small footprint: They are a personal size that fits in the palm on your hand; light weight, less than 1 kg.
DC 12V or DC 24V power input, built-in over temperature protection device, suitable for car power supply.
Temperature deflection adjusting meets with different demands.
Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com