



LABORATORY VERTICAL AUTOCLAVE BEM-20802

LABORATORY VERTICAL AUTOCLAVE BEM-20802

VERTICAL PRESSURE AUTOCLAVE



Standard built-in printer.

Deionized water interface for supplying steam generators.

Rapid water cooling system for efficient and safe sterilization of liquids.

With a quick maintenance window, the electrical parts can be repaired without removing the cover.

Microcomputer control. Fully automatic control water injection, temperature rise, sterilization, exhaust.

LCD screen displays pressure, temperature, time, running status, error codes etc.

Mobile probe detects to ensure the internal temperature of liquid directly, to ensure the sterilization effect of liquid program.

The air compressor can be optional.

SPECIFICATIONS

Model	BEM-20802
Capacity	75L
Sterilization Temperature	105°C~136°C
Working Pressure	0.23 MPa
Features	
Designed Pressure	0.28MPa
Designed Temp.	150°C
Working Temp.	105°C~136°C
Temp. Precision	0.1°C
Chamber Material	S30408
Chamber Size	φ386*670mm
Basket	φ365*360mm, 1pc
Noise	≤65dB
Altitude	≤2700m, please make a note when placing an order between 1000~2700 meters
Standard Accessories	Printer, mesh bottom basket
Optional Accessories	Air compressor
Consumption	5.5KW
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 50/60Hz(Optional);Wiring method:Air switch
External Size(W*D*H)	700*610*1070mm
Net Weight	132kg
Package Size(W*D*H)	820*740*1380mm
Gross Weight	147kg
Alt Name	Vertical Pressure Autoclave

FEATURES

Standard built-in printer.

Deionized water interface for supplying steam generators.

Rapid water cooling system for efficient and safe sterilization of liquids.

With a quick maintenance window, the electrical parts can be repaired without removing the cover.

Microcomputer control. Fully automatic control water injection, temperature rise, sterilization, exhaust.

LCD screen displays pressure, temperature, time, running status, error codes etc.

Mobile probe detects to ensure the internal temperature of liquid directly, to ensure the sterilization effect of liquid program.
The air compressor can be optional.
It is equipped with a liquid program, a medium program, and a solid program.

APPLICATIONS

Autoclave is the use of pressure saturated steam to carry out rapid and reliable disinfection and sterilization equipment, suitable for medical and health undertakings, scientific research, agriculture and other units. Sterilize medical instruments, dressings, glassware, solution media, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com