



LABORATORY VERTICAL AUTOCLAVE BEM-21405

LABORATORY VERTICAL AUTOCLAVE BEM-21405

VERTICAL AUTOCLAVE



The hand wheel slides to open the door, which is fast and labor-saving. Casters facilitate the movement of the equipment. It has a fast maintenance window, and the electrical part does not need to remove the cover for maintenance. Steam generation method: heating inside the main body, no external steam source is required. Self-expanding silicone sealing rings have a good sealing effect and long service life. It is molded with transparent medical silicone. Real-time detection and display of the temperature in the sterilization chamber, with a display accuracy of 0.1°C. The LED digital tube displays temperature, time, alarm code and the indicator light shows the current operating status.

SPECIFICATIONS

Model	BEM-21405
Capacity	150L
Sterilization Temperature	50~134°C
Working Pressure	0.217 MPa
Features	
Designed Pressure	0.3MPa
Designed Temp.	137°C
Temp. Precision	0.1°C
Chamber Material	S30408
Chamber Size	φ500*760mm
Basket/ Mesh Bottom Basket/ Bucket	φ470*230mm, 3pcs
Noise	≤65dB
Altitude	≤2700m
Standard Accessory	Basket
Optional Accessories	Printer
Consumption	6KW
Power Supply	AC380V,50/60Hz(Standard);AC220V,50/60Hz(Optional)Wiring method:Air switch
External Size(W*D*H)	630*700*1400mm
Net Weight	162kg
Package Size(W*D*H)	760*800*1530mm
Gross Weight	213kg
Alt Name	Vertical Autoclave

FEATURES

The hand wheel slides to open the door, which is fast and labor-saving. Casters facilitate the movement of the equipment. It has a fast maintenance window, and the electrical part does not need to remove the cover for maintenance. Steam generation method: heating inside the main body, no external steam source is required. Self-expanding silicone sealing rings have a good sealing effect and long service life. It is molded with transparent medical silicone. Real-time detection and display of the temperature in the sterilization chamber, with a display accuracy of 0.1°C. The LED digital tube displays temperature, time, alarm code and the indicator light shows the current operating status. Using gravity displacement and positive pressure pulsating exhaust method to discharge the cold air in the load and sterilization

room.

Optional printer to record the temperature during sterilization.

Inner water tank

A variety of programs

There are exposed programs, packaging program, rubber program, dressing program, liquid program, liquid customization, solid customization.

APPLICATIONS

It is widely used in laboratories, inspection departments, food processing enterprises, etc. for sterilization of equipment and medical waste. It uses gravity displacement to discharge the cold air in the sterilization chamber to ensure the sterilization effect.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com