



PORTABLE AUTOCLAVE BEM-21602

PORTABLE AUTOCLAVE BEM-21602

PORTABLE AUTOCLAVE



The self-expanding sealing ring has good sealing performance and can effectively prevent steam leakage.

Over-temperature and over-pressure automatic protection.

Immersion electric heating tube, high thermal efficiency, durable stainless steel tube.

Equipped with a water level gauge, if the water level is too low, it will automatically stop heating(anti-dry type).

Electric heating or liquefied petroleum gas heating(dual-use type).

With self-adjustment function, temperature and time can be adjusted by itself, automatically stop heating and alarm function after sterilization(timing control type).

Two safety valves keep double safety(timing control type).

SPECIFICATIONS

Model	BEM-21602
Capacity	18L
Sterilization Temperature	129°C
Working Pressure	0.165 MPa
Features	
Type	Anti-dry Type
Rated Working Pressure	0.14MPa
Rated Working Temp.	126°C
Temp. Setting	Fixed 126°C
Heating Method	Electricity
Sterilizing Time	Manual timing
Chamber Size	Φ280*350mm
Altitude	
Disinfection Tank	Φ265*265mm
Automatic Control	No
Low Water Level Power Off Mode	Water level switch
Consumption	2KW, 1.5KW can be customized
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 50/60Hz(Optional)
External Size(W*D*H)	450*340*600mm
Net Weight	13.5kg
Package Size(W*D*H)	400*400*670mm
Gross Weight	14.5kg
Alt Name	Portable Autoclave

APPLICATIONS

It's mostly suitable for sterilization of surgical, dental instruments, glassware, culture medium and biological dressing, food and goods, etc.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com