BioLAB

PRODUCT CATALOG



AUTOMATIC URINE ANALYZER BEM-41901

CE ISO9001 CERTIFIED

www.biolabscientific.com

URINE ANALYZER BEM-41901

AUTOMATIC URINE ANALYZER



1. Built-in 10.1-inch touch screen, built-in thermal printer.
2. Sample delivery, injection, droplet, analysis and report output are completed automatically by the instrument.
3. A high-precision sample dispenser is used to ensure thorough reaction and improve the accuracy of test results.
4. Automatic strip selection chamber, accommodating 600 test strips at the same time.
5. Supports closed puncture analysis, greatly improving biosafety.

SPECIFICATIONS

Model	BEM-41901
Cascade Function	No
Principle	Photoelectric colorimetry
Throughput	240 tests/hour
Screen	10.1-inch touch screen
Memory	Can store more than 1,000,000 test reports
Printer	Built-in thermal printer
Interface	USB, RS232, network interface
Barcode Scanner	Can be optional
Range of Application	9, 10, 11, 14 test strip
Items	9 test strip: GLU, BIL, KET, pH, BLD, PRO, URO, NIT, LEU10 test strip: GLU, BIL, KET, SG, pH, BLD, PRO, URO, NIT, LEU11 test strip: GLU, BIL, KET, SG, pH, BLD, PRO, URO, NIT, LEU, VC14 test strip: GLU, BIL, KET, SG, pH, BLD, PRO, URO, NIT, LEU, VC, CRE, CAL, MCA
Sample Rack Capacity	100pcs samples(10pcs test tube racks)
Reagent Tank Capacity	600pcs
Data Retrieval	Can be searched by actual date, range date, urine sample number, name, barcode, etc.
Automatic Sensing	Automatically detects and analyzes after placing the sample
Calibration Function	Yes
Power	130W
Power Supply	AC100~240V, 50/60Hz
External Size(W*D*H)	662*730*520mm
Net Weight	53kg
Packing Size(W*D*H)	805*600*1160mm
Gross Weight	88kg
Alt Name	Automatic Urine Analyzer



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com