BioLAB

PRODUCT CATALOG



ELISA MICROPLATE READER BEM-42205

CE ISO9001 CERTIFIED

www.biolabscientific.com

MICROPLATE READER BEM-42205

ELISA MICROPLATE READER



1. 10.1-inch large touch screen operation.
2. High precision and accurate results.
3. Software: Single wavelength and double wavelengths detection methods.

SPECIFICATIONS

Model	BEM-42205
Measurement Channel	Vertical 8 optical channels
Plate Type	96-well microplate
Wavelength Range	340~850nm
Filter	Standard 5 wavelengths of 340, 405, 450, 492, 630nm
Linear Range	0.000~3.500Abs
Reading Range	0.000~4.000Abs
Resolution	0.0001Abs
Repeatability	CV≤0.2%
Stability	≤±0.003Abs/10min
Sensitivity	≥0.01L/mg
Channel Difference	≤0.02Abs
Vibration Plate Function	5 kinds of vibration plate function, adjustable 0~255s
Incubation Function	Temp. Range: RT+4℃~50℃
Software (Standard) :	
Detection Mode	Single/double wavelength
Qualitative	Open CUT-OFF decision formula, supporting the input of judgment condition, validity condition input, grey area setting and other functions
Quantitative	Support linear, semi-log, natural logarithm, log-log, point-to-point, four-parameter equation and other quantitative analysis fitting algorithms
Display	10.1-inch color touch capacitive screen
Operating Mode	Touch screen operation, equipped with capacitive stylus, EL10DAsupport for external keyboard and mouse
Printer(Optional)	Support external USB, RJ45 network port and other universal interface printer(A4 printer can be optional)
Interface	USB 2.0*4, RJ45 network port*1, RS-232*1
Power Supply	AC100~240V, 50/60Hz
Instrument Size(W*D*H)	495*340*370mm
Package Size(W*D*H)	610*440*475mm
Net/Gross Weight	12/14kg
Alt Name	ELISA Microplate reader



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com