BioLAB

PRODUCT CATALOG



BLOOD COAGULATION ANALYZER BEM-42402

CE ISO9001 CERTIFIED

www.biolabscientific.com

AUTO COAGULATION ANALYZER BEM-42402

BLOOD COAGULATION ANALYZER



1. Dual-channel independent detection, can analyze different items at the same time.
2. 5-inch high-definition touch screen, easy to operate.
3. Open system, good compatibility, Supports reagents of various specifications.
4. 20,000 results storage.
5. Equipped with multiple pre-temperature positions to improve detection efficiency.
6. Built-in thermal printer.
7. The pipette automatically triggers the measurement, and the measurement time can be accurate to tenths of a second.
8. Less reagent consumption.

SPECIFICATIONS

Model	BEM-42402
Test Principle	Optical colorimetry
Test Items	PT, APTT, TT, FIB
Test Channel	4(can test different projects at the same time)
Wavelength	470nm
Detection Time	Normal sample detection time is 20 to 40 seconds, and can be set arbitrarily from 20 to 99 seconds
Sample Incubation Position	24
Reagent Incubation Position	6
Detection Position Temperature	37.0±1.0℃
Incubation Position Temperature	37.0±1.0℃
Incubation Time	1~999s
Reaction Time	1~99s
Reagent Dosage	Minimum dosage 20μl
Sample Volume	20μl~40μl
Display	7-inch high-definition color touch screen
Storage	200,000 results storage, automatically save measurement data when power off
Communication Interface	RS232 serial interface, support LIS system
Printer	Built-in thermal printer
Power Supply	AC100~240V, 50/60Hz
Consumption	70VA
Ambient Temperature	10℃~30℃
Relative Humidity	≤80%
Atmospheric Pressure	86kPa~106kPa
External Size(W*D*H)	390*250*135mm
Net Weight	4.96kg
Package Size(W*D*H)	445*305*265mm
Gross Weight	7kg
Alt Name	Blood Coagulation Analyzer



Biolab Scientific Ltd.
Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com