



VERTICAL LAMINAR AIRFLOW BEM1BF2 (BLVR-302)

VERTICAL LAMINAR AIRFLOW BEM1BF2

VERTICAL LAMINAR FLOW CABINET - DOUBLE SIDES TYPE



LED Display, Microprocessor control system.

UV Lamp, Emission of 253.7 nanometers for most efficient decontamination

Double Sides, Double sides work bench, operators can sit face to face.

1. With memory function in case of power-failure.

2. Double sides work bench, 2~4 operators can work together.

SPECIFICATIONS

Model	BEM1BF2
Old Model	BLVR-302
External Size (W*D*H)	1440*660*1770mm
Internal Size (W*D*H)	1340*560*545mm
Work Surface Height	750mm
Display	LED Display
Airflow Velocity	Average of 0.3~0.5m/s
Material	Main Body: Cold-rolled steel with anti-bacteria powder coatingWork Table: 304 stainless steel
Pre-Filter	Polyester fiber, washable
HEPA Filter	99.995% efficiency at 0.3μm
Noise	<65dB
Front Window	Manual, 5mm toughened glass, anti-UV
Max Opening	310mm
UV Lamp	30W*1Emission of 253.7 nanometers
LED Lamp	16W*1
Consumption	600W
Caster	Universal caster with leveling feet
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz
Standard Accessory	LED lamp, UV lamp*2, Base stand
Optional Accessory	Electric height adjustable base stand
Gross Weight	186kg
Package Size (W*D*H)	1590*890*1340mm
Alt Name	Vertical Laminar Flow Cabinet - Double Sides Type

FEATURES

LED Display, Microprocessor control system.



UV Lamp, Emission of 253.7 nanometers for most efficient decontamination



Double Sides, Double sides work bench, operators can sit face to face.



1. With memory function in case of power-failure.
2. Double sides work bench, 2~4 operators can work together.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com