





AIR SHOWER BEM1CK2 (BASB-102)





AIR SHOWER BEM1CK2

AIR SHOWER



- 1. Photoelectric sensor, automatic blowing.
- 2. Adopt with circulation wind to ensure the cleanness of shower area under non-shower status.
- 3. Double doors by electric interlock.
- 4. LED display with adjustable blowing time (0~99s).
- 5. HEPA Filter, Class 100 cleanness.

SPECIFICATIONS

Model	BEM1CK2
Old Model	BASB-102
External Size(W*D*H)	1500*1000*2050mm
Internal Size(W*D*H)	800*900*1930mm
HEPA Filter	99.995% efficiency at 0.3µm
Spraying Wind Speed	25m/s
Air Shower Time	0~99s(adjustable)
No.of SS Nozzles	12
Fluorescent Lamp	12W*1
Consumption	1100W
Cabinet Material (Optional)	1. Full cold-rolled steel with powder coating.2. Internal stainless steel, external with cold-rolled steel.3. Full stainless steel.
Door Material (Optional)	1.Cold-rolled steel with powder coating.2. Stainless steel.
Chassis	Stainless steel.
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz
Gross Weight	400kg
Package Size(W*D*H)	1600*1200*2200mm
Alt Name	Air Shower







APPLICATIONS

Air shower is a necessary passage for people entering clean room in order to minimize the amount of particulate contaminant, to achieve workplace strict clean purification standards. Personnel move through the air shower while particulate contaminants are blown off by the clean high-speed air. Then the dust cannot be brought into clean area.



Biolab Scientific Ltd.