



## MICROWAVE DIGESTER BEM2BN1 (BMWD-204)

# MICROWAVE DIGESTER BEM2BN1

## GRAPHITE DIGESTER



- \* Anti-corrosion design: TEFLON coating on the surface, acid/alkali proof.
- \* Heating uniform and fast: Adopt graphite block(antioxidant), heating faster and energy transfer faster, temperature between holes more uniform.
- \* Safety protection: adopt unique air duct insulation tech, keep the temperature ultralow, protect operator

## SPECIFICATIONS

Model	BEM2BN1
Old Model	BMWD-204
Temperature Range	RT +5~450°C
Temperature Accuracy	±1°C(450°C)
Heating Method	Infrared heating and high-purity graphite conduction
Heating Insulation Method	Unique air duct insulation technology
Digestion Tube Capacity	300ml
Max. Capacity	20pcs/batch
Power Supply	AC 220 V±10%, 50HZ
Power Consumption	3600W
External Size(W*D*H)	515*458*730mm
Package Size(W*D*H)	890*600*630mm
Gross Weight	57Kg
Alt Name	Graphite Digester

## APPLICATIONS

Graphite Digester adopts globally advanced high-temperature infrared radiation heating technology and microprocessor control platform, accurate temperature control and quick temperature rise. It has two kinds of temperature rise mode: linear and curve temperature rise mode, and offers 20 digestion programs for control of temperature rise curves.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)