



MICROWAVE DIGESTER BEM2CJ1 (BMWD-201)

MICROWAVE DIGESTER BEM2CJ1

MICROWAVE DIGESTER

More than ten safety protection systems, such as a temperature control system, pressure control system, explosion-proof security doors, and thickened cavities with multi-layer TEFLON coating, are in place to assure experiment safety. High-powered exhaust system; anytime suspend/start of programme.



Video monitoring function.

More than ten safety protection measures to ensure experiment safety, including temperature control system, pressure control system, explosion-proof security doors, thicken cavy with multi-layer TEFLON coating.

High-power exhaust system, program with suspend or start at any time.

SPECIFICATIONS

Model	BEM2CJ1
Old Model	BMWD-201
Vessel Quantity	12
Vessel Volume	100 mL
Vessel Pressure Capacity	80 MPa
Cavity	48 L Resonant Cavity
Microwave Cavity Material	SS316 with 10 layers Teflon
Teflon Coating	10 layers
Digestion Method	50 preinstalled methods, programmable 100 methods
Maximum Working Temperature	305 °C
Temperature Control Accuracy	±0.1 °C
Pressure Accuracy	±0.01 MPa
Temperature Sensor	Optical Fiber Sensor
Cooling Method	Forced air cooling
Interface	USB, RS232
Maximum Output Power	1600 W
Power Supply	AC220V ± 10%, 50Hz
External Size (WxDxH)	600x685x660 mm
Weight	105 kg
Accessory	2.5 kg (820x300x130 mm); 5.5 kg (540x480x170 mm); 12.5 kg; 2.5 kg (480x550x300 mm)
Alt Name	Microwave Digester

APPLICATIONS

Pharmaceutical Analysis, Agricultural, Environmental Analysis, Biological Sciences



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com