



## LABORATORY HORIZONTAL AUTOCLAVE BEM2T2

# LABORATORY HORIZONTAL AUTOCLAVE BEM2T2

## HORIZONTAL PULSE VACUUM AUTOCLAVE

The pulse vacuum autoclave extracts vacuum and fills steam into the sterilization room for many times to make the sterilization chamber reach a certain vacuum degree, and then fills saturated steam to reach the set pressure and temperature, so as to achieve the purpose of sterilization of the sterilized substance. It is suitable for the sterilization of solid instruments, type-A hollow-cavity instruments, implantable instruments, dressing fabrics, rubber catheters, non-sealed liquid items, etc.



1. Sterilization data output: standard micro printer, no need for separate external connection.
2. 7-inch color LCD touch screen, which can display information such as temperature, pressure, operating status, fault alarm, cause analysis, and solutions at the same time.
3. The powerful vacuum drying system has a high evacuation speed, can dry items well, and enables more thorough sterilization.
4. The air in the chamber is sterile and avoids re-contamination.
5. Adopt quick-release side cover and top cover for easy maintenance and cleaning.
6. Micro-controller programmable control technology.
7. Full protective door cover, effectively prevent burns.

## SPECIFICATIONS

Model	BEM2T2
Capacity	200L
Door	Manual
Display	7-inch LCD touch screen
Designed Pressure	-0.1/0.3MPa
Working Pressure	0.23MPa
Working Temp.	105~134°C
Temp. Precision	0.1°C
Sterilization Time	0~99min
Drying Time	0~99min
Vacuum system	Water circulating vacuum pump
Chamber Material	S30408
Chamber Size	φ500*1020mm
Altitude	≤2000m; could be customized@2000~3000m
Rack	1 mesh frame with 1 cover
Standard Accessories	Stainless steel frame with cover, mobile sensor, printer
Consumption	20kVA
Power Supply	AC380V, 50Hz(Standard); AC380V, 60Hz(Optional); AC220V, 50/60Hz(Three phase, Optional); Wiring Method: Air switch
External Size(W*D*H)	940*1040*1780mm
Net Weight	450kg
Package Size(W*D*H)	1110*1585*2080mm
Gross Weight	600kg
Alt Name	Horizontal Pulse Vacuum Autoclave

## FEATURES

1. Sterilization data output: standard micro printer, no need for separate external connection.
2. 7-inch color LCD touch screen, which can display information such as temperature, pressure, operating status, fault alarm, cause analysis, and solutions at the same time.
3. The powerful vacuum drying system has a high evacuation speed, can dry items well, and enables more thorough sterilization.
4. The air in the chamber is sterile and avoids re-contamination.
5. Adopt quick-release side cover and top cover for easy maintenance and cleaning.
6. Micro-controller programmable control technology.
7. Full protective door cover, effectively prevent burns.
8. The equipment adopt self-expanding sealing ring. Sealing performance is more reliable and stable.
9. The closing method adopts a multi-point pressing structure of the radiation rod, safe and reliable.
10. The equipment is connected to the water source without manual replenishment. After the customer chooses the program, the equipment can complete the whole process from water injection to drying without human intervention. After the program is completed, the sound prompts sterilization to be completed.
11. Built-in high speed steam generator, no external steam source, save time and effort.
12. With a mobile temperature sensor, can meet the special requirements of the laboratory.
13. Pressure, mechanical and electronic three-layer safety interlock device, with over-temperature protection and over-pressure protection.
14. It is equipped with 13 programs. The programs for exposed instruments, packaging instruments, rubber, dressings, liquids, solid DIY, liquid DIY, rapid sterilization and enhanced sterilization are sterilization programs. The BD, PCD and vacuum tests are test programs, and the drying program is an auxiliary program.



**Biolab Scientific Ltd.**

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)