



SPLIT BEAM UV VISIBLE SPECTROPHOTOMETER BEQ-2201

SPLIT BEAM UV VISIBLE SPECTROPHOTOMETER BEQ-2201

UV-VIS SPECTROPHOTOMETER



High quality silicon photometric diode detector and 1200 lines/mm diffraction grating ensure the high quality accuracy and precision.

Backlit LCD display for an easy readout.

Automatic 0A and 100%T.

Easy switching of transmittance, absorbance and concentration modes, just by pressing one key.

Direct concentration read-out and concentration factor setting function.

Large sample compartment, for 5 - 100mm path length cuvettes with optional holders.

Easy to change the halogen lamp or deuterium lamp by the user himself.

Software optional.

SPECIFICATIONS

Model	BEQ-2201
Wavelength Range	200-1000nm
Spectral Bandwidth	4nm
Wavelength Accuracy	±2nm
Photometry	Split Beam
Monochromator Type	Czerny-Turner
Focal Length	160mm
Grating	1200 lines/mm
Detector	Silicon Photocell
Wavelength Setting	Manual Turn Knob
Wavelength Repeatability	≤1nm
Stray Light	≤0.3%T(at 220nm NaI, 360nm NaNo ₂)
Photometric Range	0.0-100.0% T 0.000-1.999 A 0.000-1999 C
Photometric Accuracy	±0.5% T ±0.004 Abs (0-0.5A) ±0.008 Abs (0.5-1A)
Photometric Repeatability	≤0.2% T 0.002 Abs (0-0.5A) 0.004 Abs (0.5-1A)
Noise	100%(T) noise ≤0.3%(T) , 0%(T) noise ≤0.2%(T)
Power	AC220V±22V 50Hz±1Hz, 130W
Packaging Size	560mm X 490mm X 285mm 0.08M3 16kg
Alt Name	UV-VIS Spectrophotometer

ITEMS INCLUDED

No	Name	Quantity
1	Operation manual	1pc
2	UV WIN7 software	1pc
3	Glass cuvette 10mm	4pcs
4	Quartz cuvette 10mm	2pcs
5	Power cable	1pc
6	Fuse	2pcs
7	Cuvette holder 50mm	1pc

ACCESSORIES FOR PURCHASE

No	Name	Size
1	Cuvette holder	100mm
2	Cuvette	20mm 30mm 50mm 100mm

APPLICATIONS

Education & Teaching Laboratories

Widely used in teaching laboratories for demonstrating Beer-Lambert Law, calibration curves, and basic qualitative and quantitative analysis of colored solutions.

Chemical & Industrial Process Control

Measuring absorbance-based color intensity and tracking reaction kinetics in dyes, coatings, inks, and electroplating solutions for routine industrial quality control.

Pharmaceutical & Biotech Quality Control

Used for quantitative analysis of APIs and finished products with visible absorbance, dissolution testing, and optional basic DNA/protein quantification and reaction kinetics monitoring via PC software.

Water & Environmental Analysis

Used for routine colorimetric determination of ammonia nitrogen, total phosphorus, Cr, nitrite, and volatile phenols in environmental water quality monitoring.

Food & Agricultural Quality Control

For colorimetric detection of nitrite, nitrate, phosphate, peroxide value, and pigments in food and agricultural products for quality control compliance.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com