



SPLIT BEAM UV VISIBLE SPECTROPHOTOMETER BEQ-2601

SPLIT BEAM UV VISIBLE SPECTROPHOTOMETER BEQ-2601

SPLIT BEAM UV-VIS SPECTROPHOTOMETER

This series Split Beam UV-VIS Spectrophotometer survey optical system, and blazed holographic gratings. They have outstanding test precision and very competitive prices. and blazed holographic gratings. Its 8-inch color touchscreen supports quantitative, kinetic and multi-wavelength analysis, while this adds full-spectrum scanning for more advanced spectral applications.



Linear regression.
Detailed spectrum scanning.
Concentration on direct reading.
Time-based kinetics determination.
Peak / Valley detecting.
GOTO λ .
Multi-wavelength measurement.
Split beam optical system.
Automatic wavelength settings.
8-inch multi-color touch-screen.
Automatic 8-position cuvette holder.
Automatic zero and full-scale adjustment.

SPECIFICATIONS

Model	BEQ-2601
Wavelength Range	190-1100nm
Spectral Bandwidth	1.8nm
Wavelength Accuracy	$\pm 0.3\text{nm}$
Photometry	Split Beam
Monochromator Type	Czerny-Turner
Focal Length	160mm
Grating	1200 lines/mm
Detector	Silicon Photocell
Wavelength Setting	8-inch color touch-screen
Wavelength Repeatability	$\leq 0.1\text{nm}$
Stray Light	$\leq 0.03\%T$ (at 220nm NaI, 360nm NaNo ₂)
Photometric Range	0.0-200.0% T-0.301-4.000 A0.000-9999 C
Photometric Accuracy	$\pm 0.3\% T \pm 0.002 \text{ Abs (0-0.5A)} \pm 0.004 \text{ Abs (0.5-1A)}$
Photometric Repeatability	$\leq 0.15\% T 0.001 \text{ Abs (0-0.5A)} 0.002 \text{ Abs (0.5-1A)}$
Noise	100%(T)noise $\leq 0.15\%(T)$, 0%(T)noise $\leq 0.1\%(T)$
Power	AC220V $\pm 22\text{V}$ 50Hz $\pm 1\text{Hz}$, 200W
Packaging Size	710mm X 590mm X 505mm 0.21M3 40kg
Alt Name	Split Beam UV-VIS Spectrophotometer

ITEMS INCLUDED

No	Name	Quantity
1	Operation manual	1pc
2	Glass cuvette 10mm	4pcs
3	Quartz cuvette 10mm	2pcs
4	Power cable	1pc
5	Cuvette holder 10mm	

ACCESSORIES FOR PURCHASE

No	Name	Size
1	UV WIN8 station pro software	
2	Cuvette holder	50mm 100mm
3	Cuvette	20mm 30mm 50mm 100mm

FEATURES

Linear regression.
Detailed spectrum scanning.
Concentration on direct reading.
Time-based kinetics determination.
Peak / Valley detecting.
GOTO λ .
Multi-wavelength measurement.
Split beam optical system.
Automatic wavelength settings.
8-inch multi-color touch-screen.
Automatic 8-position cuvette holder.
Automatic zero and full-scale adjustment.
Equipped with a USB port.
Software optional.

APPLICATIONS

Education & Teaching Laboratories

Widely used in teaching laboratories for demonstrating Beer-Lambert Law, calibration curves, and basic qualitative and quantitative analysis of colored solutions.

Chemical & Industrial Process Control

Measuring absorbance-based color intensity and tracking reaction kinetics in dyes, coatings, inks, and electroplating solutions for routine industrial quality control.

Pharmaceutical & Biotech Quality Control

Used for quantitative analysis of APIs and finished products with visible absorbance, dissolution testing, and optional basic DNA/protein quantification and reaction kinetics monitoring via PC software.

Water & Environmental Analysis

Used for routine colorimetric determination of ammonia nitrogen, total phosphorus, Cr, nitrite, and volatile phenols in environmental water quality monitoring.

Food & Agricultural Quality Control

For colorimetric detection of nitrite, nitrate, phosphate, peroxide value, and pigments in food and agricultural products for quality control compliance.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com