



BOD INCUBATOR BER-2105

BOD INCUBATOR BER-2105

COOLING INCUBATOR/REFRIGERATED INCUBATOR/ BOD INCUBATOR



1. Unique internal wind circulation structure design, breeze circulate fan make inner chamber temperature uniformity.
2. Double door seal; tempered glass silicon rubber seal inner door and magnetic rubber seal outer door, which are convenient to on/off; inner chamber with light for convenient observation. .
3. Intelligent defrosting function ensure device long-time run without frost.
4. Fluoride-free refrigeration and gentle breeze circulation.
5. Test hole of $\Phi 52\text{mm}$ at left side of container.

SPECIFICATIONS

Model	BER-2105
Cycle Mode	Forced Convection
Function	
--Temp. Range	0-65°C
--Temp. Resolution Ratio	0.1°C
--Temp. Motion	High Temp: $\pm 0.5^\circ\text{C}$, Low Temp: $\pm 1^\circ\text{C}$
--Temp. Uniformity	$\pm 1.5^\circ\text{C}$
Structure	
--Inner Chamber	Mirror Stainless Steel
--Outer Shell	Cold rolling steel electrostatic spraying exterior
--Insulation Layer	Polyurethane
--Heater	Stainless steel heater
--Power Rating	1.0kW
--Compressor	Air cooled hermetic compressor
--Cryogen	R134a
--Defrost Structure	Automatic control intelligent defrosting
--Test Hole	Inner diameter 43mm (one)
--Controlled External Power Supply	Outer universal socket (one), inner waterproof socket (one)
--Temp. Control Mode	30-stage LCD program
--Temp. Setting Mode	Touch button setting
--Temp. Display Mode	Measuring temperature: LCD upper row; Setting temperature: LCD lower row
--Timer	0-99.9h*30 segment (with timing wait function)
--Operation Function	Program operation
--Sensor	PT100
--Additional Function	Loop self-diagnosis, sensor fault alarm
Safety Device	Over temperature alarm
Specification	
--Inner Chamber Size (W*L*H)(mm)	490*400*750
--Exterior Size (W*L*H)(mm)	646*641*1301
--Packing Size (W*L*H)(mm)	751*730*1490

--Volume	150L
--Load Per Rack	15kg
--Shelf Number	9
--Shelf Space	60mm
--Power Supply Current Rating	AC220V/3.6A
--NW/GW (kg)	86/114
Accessory	
--Shelf	2
--Shelf Frame	4
Optional Accessories	Shelf, RS485 port, printer, recorder, Remote Control, wireless messaging alarm, U-Disk data storage
Alt Name	Cooling Incubator/Refrigerated Incubator/ Bod Incubator



APPLICATIONS

Various constant temperature experiments and environmental tests at 0~65C, water analysis, microbe culture of BOD / bacteria, plant breeding, and sample preservation.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com