



MUFFLE BOX FURNACE BER-3414

MUFFLE BOX FURNACE BER-3414

1700°C CERAMIC FIBER MUFFLE FURNACE



1. Mirror stainless steel furnace mouth, long-term use will not change color.
2. -forming polycrystalline mullite fiber furnace, high efficiency insulation.
3. Double shell, the air sleeve heat insulation, and double air guiding passage .
4. High-purity silicon--molybdenum rod heating, and with standard exhaust chimney.
5. High precision program controller, with imported sensor and imported voltage regulating module.
6. With leakage protection, thermocouple failure, door opening electrical outage, over-temperature protection and sound-light alarm safety device.
7. Lockable handle, quick detachable structure,easy to maintenance and repair.
8. Standard with insulated gloves, crucible tongs and Alumina load bearing board

SPECIFICATIONS

Model	BER-3414
Function	
--Temp. Range	Max 1700°C (Long time continuous working temperature 1650°C)
--Temp. Accuracy	± 1°C
--Temp. Resolution Ratio	1°C
--Temp. RISING Time To Max Temp	≤140min
Structure	
--Furnace Body	HHR Polycrystalline Mullite Fiber
--Outer Shell	Cold rolling steel with electrostatic Spraying exterior
--Chamber Size	150*150*150
--Exhaust Hole	Di Φ 22, De Φ 18
--Heater	Silicon Molybdenum Rod
--Heating Power	5.5KW
Controller	
--Temp. Control	7.0 inch touch screen program controller, with curve viewing and USB data storage functions.
--Temp. Control Mode	Intelligent Microcomputer PID Control
--Display Mode	Touch Type Operation
--Timer	0~9999min
--Operation Function	Constant Value Operation Or Program Operation
--Sensor	S-type Thermocouple
--Additional Function	Heating Start Stop Button, Sensor Fault Alarm, Temperature Overshoot Self Setting, Temperature Correction
--Safety Device	Over temperature Alarm, Leakage Protection, Door Opening Heating
Specification	
--Exterior Size (W*L*H)(mm)	600*815*1100
--Packing Size (W*L*H)(mm)	760*985*1310
--Volume	4L
--Current Rating (50/60HZ)	AC220V 50Hz
--Nw/Gw (kg)	80/100
Optional Type	485 Communication, U Disk Data Storage



FEATURES

1. Mirror stainless steel furnace mouth, long-term use will not change color.
2. -forming polycrystalline mullite fiber furnace, high efficiency insulation.
3. Double shell, the air sleeve heat insulation, and double air guiding passage .
4. High-purity silicon--molybdenum rod heating, and with standard exhaust chimney.
5. High precision program controller, with imported sensor and imported voltage regulating module.
6. With leakage protection, thermocouple failure, door opening electrical outage, over-temperature protection and sound-light alarm safety device.
7. Lockable handle, quick detachable structure,easy to maintenance and repair.
8. Standard with insulated gloves, crucible tongs and Alumina load bearing board.

APPLICATIONS

It is used for sintering, melting and analyzing metal, nonmetal and other compound materials in laboratories of universities, research institutes and industrial and mining enterprises.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com